



# ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

802 West Main  
75652-4459, TX Henderson  
Phone: 903-657-1517  
Fax: 903-657-0253



## 1547 Straight Blade Rubber Conn 15A 125V 5-15R

*Pass & Seymour/Legrand*

|                  |  |
|------------------|--|
| Catalog Number   | 1547   |
| Manufacturer     | Pass & Seymour/Legrand   |
| Description      | Straight Blade Plug, 15 A, 125 V, 2 Poles, 3 Wires, Yellow, -40 °C Operating Temperature, +75 °C Operating Temperature, Screw Terminal, 1.58 In Diameter, 3.10 In Length, #18 to #10 Awg Wire Size, Corrosion Resistant, Impact Resistant, Oil Resistant, Chemical Resistant, Heat Resistant, Weather Resistant, 0.26 LB |
| Weight per unit  | 0.2560 (lbs/each)  |
| Product Category | Plugs, Connectors, Inlets, Out   |

### Features

|                 |         |
|-----------------|---------|
| amperage rating | 15      |
| indoor/outdoor  | Indoor  |
| Poles           | 2       |
| Voltage         | 125.0 V |
| Voltage Rating  | 125     |

### Dimensions and Weight

|      |       |
|------|-------|
| Size | 3.25" |
|------|-------|

### Descriptions

|                        |   |
|------------------------|---|
| Description            | STRAIGHT BLADE RUBBER CONN 15A 125V 5-15R |
| extra long description | P&S 1547 STR BLD RUBBER CONN 15A 12       |

### Manufacturer Information

|       |                  |
|-------|------------------|
| Brand | Pass and Seymour |
| GTIN  | 00785007114126   |
| UPC   | 785007114126     |

### Taxonomies, Classifications, and Categories

|                      |                             |
|----------------------|-----------------------------|
| Category Description | Residential cord connectors |
| Type                 | CONNECTOR                   |

### Trade Size

|          |      |
|----------|------|
| Amperage | 15.0 |
|----------|------|

### Packaging

|                 |       |
|-----------------|-------|
| Carton          | 1     |
| Package         | 20    |
| Weight Per each | 0.256 |

### Uses, Certifications, and Standards

|          |                |
|----------|----------------|
| standard | UL, CSA, UL498 |
|----------|----------------|