



# ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

760 Ford St.  
80915-0000, CO Colorado Springs  
Phone: 719-559-2456  
Fax: 719-867-4287



## 2107 120/277V 2000W SPST Conduit Mount Die Cast Zinc

*Nsi Industries*

|                  |  |
|------------------|--|
| Catalog Number   | 2107   |
| Manufacturer     | Nsi Industries   |
| Description      | Conduit Mount, 208 to 277 V, 2000 W, 2 In Width, 3-3/4 In Height, Die Cast Zinc Housing Material, SPST Switch Type, Cadmium Coated CDS Photocell Sensor, -40 °F Operating Temperature, +140 °F Operating Temperature, Conduit Mount, 0.6 LB/Ea |
| Weight per unit  | 0.6000 (lbs/each)  |
| Product Category | Lighting Photocells  |

### Features

|                |             |
|----------------|-------------|
| supply voltage | 120-277 VAC |
| Timing Range   | 2 Minutes   |

### Dimensions and Weight

|      |                    |
|------|--------------------|
| Size | .500 Conduit Mount |
|------|--------------------|

### Descriptions

|             |   |
|-------------|---|
| Description | 120/277V 2000W SPST CONDUIT MOUNT DIE CAST ZINC |
|-------------|---|

### Manufacturer Information

|      |                |
|------|----------------|
| GTIN | 00786261600318 |
| UPC  | 786261600318   |

### Taxonomies, Classifications, and Categories

|      |                            |
|------|----------------------------|
| Type | Die Cast Zinc Photocontrol |
|------|----------------------------|

### Availability

|                     |          |
|---------------------|----------|
| Manufacturer Status | Inactive |
| Status              | Inactive |

### Packaging

|                 |     |
|-----------------|-----|
| Carton          | 1   |
| Weight Per each | 0.6 |

### Uses, Certifications, and Standards

|                          |   |
|--------------------------|---|
| Application              | Parking Lot-Building Perimeter-Outdoor Signage Lighting |
| Enclosure                | Zinc Diecast  |
| environmental conditions | -40 to + 140 F  |
| Frequency Rating         | 50-60 Hz  |
| Mounting                 | Conduit Mount   |
| Operating Temperature    | -40 to + 140 F  |
| standard                 | UL-CSA  |