



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

10101 SH 30
77845-0000, TX College Station
Phone: 979-779-6630
Fax: 979-779-6620



269RFS LBR6 ALO2 SWW1 Ar LSS MWD Mvolt Ugz *Lithonia Lighting - Acuity*

Catalog Number	269RFS
Manufacturer	Lithonia Lighting - Acuity
Description	LBR Is Everything You Need In A Downlight At An Affordable Price. Whether It'S The Seamless Install From-Below Design, Abundant Energy Savings or Maintaining Glare-Free Aesthetics, LBR Is The Perfect Solution For Any Renovation, Remodel or New Construction Project.
Weight per unit	3.7 (lbs/each)
Product Category	Lighting

Features

average life	60,000
dimensions	1000 LM,1500 LM,2000 LM,Switchable
dimnable	Yes
Lamp Included	Yes
Lamp Type	LED - Static
lumens	1000 LM,1500 LM,2000 LM,Switchable
Maximum Operating Temperature	25
Power Source	Hardwired
Shape	Round
Voltage Rating	120-277
Warranty	5
Wattage	25.6

Material, Color, and Finish

Color	Clear
color rendering index (cri)	80
color temperature	Variable
Finish	Semi-Specular

Descriptions

Construction	New Construction,Retrofit
extra long description	LITH LBR6 ALO2 SWW1 AR LSS MWD MVOL
Features	Design Select
Long Description	LBR is everything you need in a downlight at an affordable price. Whether it's the seamless install from-below design, abundant energy savings or maintaining glare-free aesthetics, LBR is the perfect solution for any renovation, remodel or new construction project.
Product Type	Retrofit Kit



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

10101 SH 30
77845-0000, TX College Station
Phone: 979-779-6630
Fax: 979-779-6620

Manufacturer Information

Brand	Lithonia Lighting
GTIN	00194994846499
Manufacturers Part Number	LBR6 ALO2 SWW1 AR LSS MWD MVOL
UPC	194994846499

Taxonomies, Classifications, and Categories

Category Description	LED ARCHITECTURAL & SPECIFICATION LIGHTING
----------------------	--

Trade Size

aperture size	6 in
---------------	------

Packaging

Carton	1
Weight	3.688
Weight Per each	3.748

Uses, Certifications, and Standards

Application	Education,Hospitality,House of Worship,Offices & Banks,Retail,Retrofit
environmental conditions	Indoor
Mounting	Recessed
standard	ULENERGY STAR,Low UGR