



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

802 West Main
75652-4459, TX Henderson
Phone: 903-657-1517
Fax: 903-657-0253



31371 Aqua-Gel II, 1-Gallon Bucket *Ideal*

Catalog Number	31371
Manufacturer	Ideal
Description	Lubricant, 1 Gal Bucket, Clear Blue, Mild Odor, Aqua-Gel II Lubricant, 0.98 Specific Gravity, +40 to +100 °F, 8.92 LB
Weight per unit	8.9 (lbs/each)
Product Category	Paint, Chemicals, Etc.

Dimensions and Weight

Size	1
------	---

Descriptions

Description	AQUA-GEL II, 1-GALLON BUCKET
extra long description	IDEAL 31-371 Aqua-Gel Lubricant, Ide
Features	IDEAL Aqua-Gel II Non-toxic cable pulling lubricant in clear blue color is a polymer-based formula that offers maximum tension reduction in high-stress electrical and communications cable-pulling operations. Lubricant dries to a semi-fluid film that won't clog conduit, and cleans up easily with soap/water. It remains temperature stable over a wide temperature range from 28°F to 180°F (-2°C to 88°C). Lubricant is convenient to apply by hand, brush or pump. It is well suited with all cable types except compo

Special Features	Polymer-based formula provides maximum tension reduction in high-stress electrical and communication cable-pulling operations; Compatible with all cable types except composite rubber; Cleans up easily with soap and water; Clings to cable throughout long pulls; Remains stable over wide temperature range; Dries to a semi-fluid film that won't clog conduit; Easy to apply by hand, brush, or pump; Environmentally safe - non-toxic, non-flammable and non-corrosive; For outdoor use only
------------------	---

Manufacturer Information

Brand	Ideal
GTIN	00783250313716
UPC	783250313716

Taxonomies, Classifications, and Categories

Category Description	WIRE LUBE, MARKERS, & TIES
Type	Lubricant



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

802 West Main
75652-4459, TX Henderson
Phone: 903-657-1517
Fax: 903-657-0253

Packaging

Carton	1
Package	4
Weight Per each	8.925

Uses, Certifications, and Standards

standard	UL Listed
----------	-----------