



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

1612 E. Booth Road
72143-0000, AR Searcy
Phone: 501-368-0309
Fax: 501-368-0619



3394043 480V 3P + G DS100 Receptacle

Meltric Corporation

Catalog Number	3394043
Manufacturer	Meltric Corporation
Description	Meltric 33-94043 Receptacle, With Ground, Short Circuit Rating 65 Kamp, Application: Metals, Quarry, Automotive and Mining Industries, Standard: UI, Csa, Nom, IEC, Ce, Nfpa 70E, Number Of Poles: 3, Number Of Wires: 4, Wire Size: 4 to 2/0AWG, Amperage Rating: 100AMP, Volta
Weight per unit	3.9 (lbs/each)
Product Category	Pin & Sleeve Devices

Features

amperage rating	100 W
Material	Polyester
Number of Wires	798
Poles	3 in
Voltage Rating	Overall Dimension 4-1/16 Inch Width x 3-3/16 Inch Depth x 4-3/4 Inch Height; Fuel Type Natural; Capacity 23000 to 290000 BTU/Hour; Pressure Tapping 1/8 Inch Threaded with Plug; Pressure Regulator Set Point 3.5 Inch WC
Wire Size	4 to 2/0 AWG

Material, Color, and Finish

Color	Blue Light
-------	------------

Dimensions and Weight

Size	4.45 DIA X 5.39 IN
------	--------------------

Descriptions

Description	480V 3P + G DS100 RECEPTACLE
extra long description	MEL 33-94043 DS100 RECEPTACLE
Long Description	Meltric 33-94043 Receptacle, With Ground, Short Circuit Rating 65 KAMP, Application: Metals, Quarry, Automotive and Mining Industries, Standard: UL, CSA, NOM, IEC, CE, NFPA 70E, Number Of Poles: 3, Number Of Wires: 4, Wire Size: 4 to 2/0AWG, Amperage Rating: 100AMP, Volta
Product Type	DS100 Receptacle
Special Features	With Ground, Short Circuit Rating 65 KAMP



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

1612 E. Booth Road
72143-0000, AR Searcy
Phone: 501-368-0309
Fax: 501-368-0619

Manufacturer Information

Brand	Meltric
GTIN	00784474022460
Manufacturers Part Number	33-94043
sub brand	Decontactor
UPC	784474022460

Taxonomies, Classifications, and Categories

Category Description	Residential GFCI devices
Type	RECEPTACLE

Packaging

Carton	1
Weight Per each	3.92

Uses, Certifications, and Standards

Application	Metals, Quarry, Automotive and Mining Industries
environmental conditions	-40 to 140 F
nema rating	NEMA 3R, IP54/IP55
standard	UL, CSA, NOM, IEC, CE, NFPA 70E