



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

5575 Ruben M Torres Blvd
78526-0000, TX Brownsville
Phone: 956-295-3007
Fax: 956-295-3008



3398043 480V 3P + G DS100 Inlet *Meltric Corporation*

Catalog Number	3398043
Manufacturer	Meltric Corporation
Description	Meltric 33-98043 Inlet, Enclosure Nema 3R, IP54/IP55, Wiring Capacity 4 to 2/0 Awg, Polarity 3 Pole, Ground, Short Circuit Rating 65 Kamp, Application: Metals, Quarry, Automotive and Mining Industries, Standard: UI, Csa, Nom, IEC, Ce, Nfpa 70E, Size: 4.45 Dia X 2.80IN, Am
Weight per unit	2.0 (lbs/each)
Product Category	Pin & Sleeve Devices

Features

amperage rating	100 W
Material	Polyester
Voltage Rating	Overall Dimension 4-1/16 Inch Width x 3-3/16 Inch Depth x 4-3/4 Inch Height; Fuel Type Natural; Capacity 23000 to 290000 BTU/Hour; Pressure Tapping 1/8 Inch Threaded with Plug; Pressure Regulator Set Point 3.5 Inch WC

Material, Color, and Finish

Color	Blue Light
-------	------------

Dimensions and Weight

Size	4.45 DIA X 2.80 IN
------	--------------------

Descriptions

Description	480V 3P + G DS100 INLET
extra long description	MEL 33-98043 DS100 INLET
Long Description	Meltric 33-98043 Inlet, Enclosure NEMA 3R, IP54/IP55, Wiring Capacity 4 To 2/0 AWG, Polarity 3 Pole, Ground, Short Circuit Rating 65 KAMP, Application: Metals, Quarry, Automotive and Mining Industries, Standard: UL, CSA, NOM, IEC, CE, NFPA 70E, Size: 4.45 DIA X 2.80IN, Am
Product Type	DS100 Inlet
Special Features	Enclosure NEMA 3R, IP54/IP55, Wiring Capacity 4 To 2/0 AWG, Polarity 3 Pole, Ground, Short Circuit Rating 65 KAMP

Manufacturer Information

Brand	Meltric
GTIN	00784474012454
Manufacturers Part Number	33-98043
sub brand	Decontactor
UPC	784474012454



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

5575 Ruben M Torres Blvd
78526-0000, TX Brownsville
Phone: 956-295-3007
Fax: 956-295-3008

Taxonomies, Classifications, and Categories

Category Description	Residential GFCI devices
Type	TRIP UNIT, INSULATED CASE TYPE; CSA APPROVAL; 800 AMPERE CURRENT RATING; INSTANTANEOUS/LONG DELAY TIME/SHORT DELAY TIME, GROUND FAULT DEFEATABLE ADJUSTMENT; MICROVERSATRIP[R] BRAND; REPLACEMENT TRIP UNIT; INCLUDES PROTECTIVE RELAY AND COMMUNICATION

Packaging

Carton	1
Weight Per each	2.02

Uses, Certifications, and Standards

Application	Metals, Quarry, Automotive and Mining Industries
standard	UL, CSA, NOM, IEC, CE, NFPA 70E
Temperature Rating	-40 to 140 F