



# ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

475 Boardwalk  
78119-2604, TX Kenedy  
Phone: 830-299-4593  
Fax: 830-583-9886



## 691 Combo 15A 1 SW 1P-120V 1RECP-125V BR

*Pass & Seymour/Legrand*

|                  |  |
|------------------|--|
| Catalog Number   | 691  |
| Manufacturer     | Pass & Seymour/Legrand   |
| Description      | Our Standard Pass and Seymour Combination Switches Allow You to Add Lights to Any Room In Your Home Without Having to Add or Replace Wall Boxes. |
| Weight per unit  | 0.2171 (lbs/each)  |
| Product Category | Combination Devices  |

### Features

|                       |  |
|-----------------------|--|
| action                | SP & Recptacle   |
| actuator              | Toggle   |
| amperage rating       | 15   |
| connection            | Side wire  |
| Contact Configuration | N-O  |
| Contact Rating        | 15 Amp, 120/125 VAC  |
| indoor/outdoor        | Indoor   |
| Load Rating           | 15 A @ 120/125 VAC   |
| Load Type             | Fluorescent, LED, Xenon, Incandescent, CFL, Halogen, Universal |
| Material              | Thermoplastic  |
| Mounting Type         | Wall Box   |
| Number of Gangs       | 1  |
| Number of Switches    | 1.0  |
| operating cycles      | 30k.0  |
| Outlet Type           | Indoor   |
| package quantity      | 1.0  |
| Poles                 | 1  |
| supply voltage        | 125.0  |
| Switch Type           | Toggle   |
| throw type            | Single Throw   |
| Voltage               | 120 VAC, 125 VAC   |
| Voltage Rating        | 120/125  |
| Wall Plate Included   | NO   |
| Wattage               | Electrical power is expressed in Amps and Volts.               |
| Wire Size             | #14 - #10 Awg  |

### Material, Color, and Finish

|        |       |
|--------|-------|
| Finish | SATIN |
|--------|-------|

### Dimensions and Weight

|      |                          |
|------|--------------------------|
| Size | 1.32 L x 0.94 W x 4.06 H |
|------|--------------------------|



# ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

475 Boardwalk  
78119-2604, TX Kenedy  
Phone: 830-299-4593  
Fax: 830-583-9886

## Descriptions

|                        |   |
|------------------------|---|
| Description            | COMBO 15A 1 SW 1P-120V 1RECP-125V BR  |
| extra long description | P&S 691 COMBO 15A 1 SW 1P-120V 1REC   |
| Features               | Combination   |
| Long Description       | Our standard Pass and Seymour combination switches allow you to add lights to any room in your home without having to add or replace wall boxes.                                |
| Product Type           | Combo 15A 1 SW 1P-120V 1RECP-125V BN  |
| Special Features       | Easily accessible break-off for separate or common feed. Side wire #12 and #14 AWG. Two devices fit into the space of one. Grounding combination devices meet NEC Requirements. |

## Manufacturer Information

|       |                  |
|-------|------------------|
| Brand | Pass and Seymour |
| GTIN  | 00785007691009   |
| UPC   | 785007691009     |

## Taxonomies, Classifications, and Categories

|                      |                             |
|----------------------|-----------------------------|
| Category Description | Residential Switches        |
| Type                 | Switch, Outlet, Combination |

## Trade Size

|          |      |
|----------|------|
| Amperage | 15.0 |
|----------|------|

## Packaging

|                 |        |
|-----------------|--------|
| Carton          | 1      |
| Package         | 50     |
| Weight Per each | 0.2171 |

## Uses, Certifications, and Standards

|                          |   |
|--------------------------|---|
| Application              | Residential/Commercial                  |
| environmental conditions | Flammability: UL94 V2                   |
| Mounting                 | WALL                                    |
| Operating Temperature    | Maximum continuous +60°C, minimum -30°C |
| standard                 | CULUS, UL20, UL498                      |