

Buzzer/Strobe

CFA Series

The Edwards 7007B-N5 Buzzer/Strobe is an audible/visual signaling device that may be used in a variety of system configurations including call for assistance applications.

Designed for installation in a single gang 2" (51mm) x 4" (102mm) box.

Features and Specifications

- Neutral white color
- 92dB at 1 meter/82dB at 10 ft.




Ordering Information

Description	Cat. No.	Operating Voltage	Current	Lens Color	dB at 1m/10ft.	Strobe Candela
Buzzer/Strobe	7007B-N5	120V AC	0.115 A	Clear	92/82	150
	7007BA-N5	120V AC	0.115 A	Amber	92/82	120
	7007BB-N5	120V AC	0.115 A	Blue	92/82	51
	7007BG-N5	120V AC	0.115 A	Green	92/82	86
	7007BR-N5	120V AC	0.115 A	Red	92/82	74

Weights and Dimensions

Cat. No.	Approx. Net Weight (lb.)	Approx. Shipping Weight (lb.)
7007B-N5	0.41	0.59
7007BA-N5	0.41	0.59
7007BB-N5	0.41	0.59
7007BG-N5	0.41	0.59
7007BR-N5	0.41	0.59



Buzzer/Strobe

CFA Series

The Edwards 7007B-N5 Buzzer/Strobe is an audible/visual signaling device that may be used in a variety of system configurations including call for assistance applications.

Designed for installation in a single gang 2" (51mm) x 4" (102mm) box.

Features and Specifications

- Neutral white color
- 92dB at 1 meter/82dB at 10 ft.




Ordering Information

Description	Cat. No.	Operating Voltage	Current	Lens Color	dB at 1m/10ft.	Strobe Candela
Buzzer/Strobe	7007B-N5	120V AC	0.115 A	Clear	92/82	150
	7007BA-N5	120V AC	0.115 A	Amber	92/82	120
	7007BB-N5	120V AC	0.115 A	Blue	92/82	51
	7007BG-N5	120V AC	0.115 A	Green	92/82	86
	7007BR-N5	120V AC	0.115 A	Red	92/82	74

Weights and Dimensions

Cat. No.	Approx. Net Weight (lb.)	Approx. Shipping Weight (lb.)
7007B-N5	0.41	0.59
7007BA-N5	0.41	0.59
7007BB-N5	0.41	0.59
7007BG-N5	0.41	0.59
7007BR-N5	0.41	0.59



6
CALL FOR ASSISTANCE