



# ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

555 E. 15th Street  
72701-0000, AR Fayetteville  
Phone: 479-443-4948  
Fax: 479-443-6465



## 7803MD 30A 3P 3 PH Ac Motor

*Pass & Seymour/Legrand*

Catalog Number	7803MD
Manufacturer	Pass & Seymour/Legrand
Description	Manual Control Switch, 3 Poles, 30 A, 600 V Ac, 1.7538 (L) X 1.825 (W) X 2.375 (H) In, Box Mount, -40 °C Operating Temperature, +75 °C Operating Temperature, Toggle Actuator, 0.335 LB
Weight per unit	0.3350 (lbs/each)
Product Category	Misc Wiring Devices

### Features

actuator	Toggle
amperage rating	30
connection	Side & Back Wired
indoor/outdoor	Indoor
load	30A
Load Rating	30 A @ 600 VAC
Load Type	CFL, Universal, Halogen, Fluorescent, Incandescent, Xenon, LED
Material	Thermoplastic
Number of Gangs	1
Number of Phases	3.0
Number of Switches	1.0
operating cycles	50000
Poles	3-way
Switch Type	Toggle
throw type	Single Throw
Voltage	600.0 V
Wall Plate Included	NO
Wire Size	#14 - #10 Awg

### Material, Color, and Finish

Finish	Matte
--------	-------

### Dimensions and Weight

Size	1.7538" Depth x 1.825" Width x 2.375" Height
------	----------------------------------------------

### Descriptions

Description	30A 3P 3 PH AC MOTOR
extra long description	P&S 7803MD 30A 3P 3 PH AC MOTOR
Special Features	Three Pole, Three Phase AC Manual Motor Controller, suitable as Motor Disconnect



# ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

555 E. 15th Street  
72701-0000, AR Fayetteville  
Phone: 479-443-4948  
Fax: 479-443-6465

## Manufacturer Information

Brand	LEGRAND-PASS & SEYMOUR
GTIN	00785007267686
Manufacturers Part Number	7803MD
UPC	785007267686

## Taxonomies, Classifications, and Categories

Category Description	POWER TOOLS
Type	Manual Controller

## Trade Size

Amperage	30.0
----------	------

## Packaging

Carton	1
Package	10
Weight Per each	0.335

## Uses, Certifications, and Standards

environmental conditions	UL94 V2
Frequency Rating	60Hz
Mounting	BOX
Operating Temperature	Maximum continuous +75°C, minimum -40°C
standard	CULUS, CSA Listed, UL Listed