



# ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

13405 Stemmons Frwy  
75234-0000, TX Farmers Branch  
Phone: 972-206-0016  
Fax: 972-352-2818



## A12301084 A12 3P Contactor 600/120V, 110/50

*Industrial Connections &*

|                  |  |
|------------------|--|
| Catalog Number   | A12301084  |
| Manufacturer     | Industrial Connections &   |
| Description      | 3 Pole, 27 Amp, Non-Reversing Across The Line Contactor With 110-120V Ac Coil and 1 No Auxiliary Contact |
| Weight per unit  | 770.0 (lbs/each)   |
| Product Category | IEC Contactors   |

### Dimensions and Weight

|      |            |
|------|------------|
| Size | 44x74x74mm |
|------|------------|

### Descriptions

|                        |  |
|------------------------|--|
| Description            | A12 3P CONTACTOR 600/120V, 110/50  |
| extra long description | ABB A12-30-10-84 A12,3P CONTR,110/5  |
| Long Description       | 3 pole, 27 amp, non-reversing across the line contactor with 110-120V AC coil and 1 NO auxiliary contact |
| Product Type           | A12, 3P Contr, 110/50, 110-120/60  |
| Special Features       | Terminal type: Screw terminals   |

### Manufacturer Information

|                           |                |
|---------------------------|----------------|
| Brand                     | ABB            |
| GTIN                      | 00662019879307 |
| Manufacturers Part Number | A12-30-10-84   |
| UPC                       | 662019879307   |

### Taxonomies, Classifications, and Categories

|                      |               |
|----------------------|---------------|
| Category Description | AC CONTACTORS |
| Type                 | Contactors    |

### Packaging

|                 |     |
|-----------------|-----|
| Carton          | 1   |
| Weight Per each | 770 |

### Uses, Certifications, and Standards

|             |   |
|-------------|---|
| Application | Mainly used for controlling 3-phase motors and generally for controlling power circuits up to 690 V AC or 220 V DC. The contactors can also be used for many other applications such as isolation, capacitor switching, lighting. |
| standard    | BV, CB, CCC, CSA, cUL, CE, DNV, RINA, RoHS, UL  |