



# ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

110 Success Blvd  
79029-0000, TX Dumas  
Phone: 806-934-4805  
Fax: 806-717-2052



## AF16301013 30A, 100-250V, 3P Contactor

*Industrial Connections &*

|                  |  |
|------------------|--|
| Catalog Number   | AF16301013   |
| Manufacturer     | Industrial Connections &   |
| Description      | 3 Poles 30 Amperes Non-Reversing Across The Line Contactor With 100-250V Ac/DC Coil and 1 No Auxilliary Contacts. 77 Millimeters Depth X 86 Millimeters Height X 45 Millimeters Width. |
| Weight per unit  | 595.0 (lbs/each)   |
| Product Category | IEC Contactors   |

### Dimensions and Weight

|      |            |
|------|------------|
| Size | 45x86x77mm |
|------|------------|

### Descriptions

|                        |  |
|------------------------|--|
| Description            | 30A,100-250V, 3P CONTACTOR   |
| extra long description | ABB AF16-30-10-13 AF16 3P CONTR, 1N  |
| Long Description       | 3 poles 30 amperes non-reversing across the line contactor with 100-250V AC/DC coil and 1 NO auxilliary contacts. 77 millimeters depth x 86 millimeters height x 45 millimeters width. |
| Product Type           | AF16 3P Contr, 1NO, 100-250VAC/D   |
| Special Features       | Terminal type: Screw terminals   |

### Manufacturer Information

|                           |                |
|---------------------------|----------------|
| Brand                     | ABB            |
| GTIN                      | 00804325538565 |
| Manufacturers Part Number | AF16-30-10-13  |
| UPC                       | 804325538565   |

### Taxonomies, Classifications, and Categories

|                      |                       |
|----------------------|-----------------------|
| Category Description | IEC/FREEDOM CONTACTOR |
| Type                 | Contactors            |

### Packaging

|                 |     |
|-----------------|-----|
| Carton          | 1   |
| Weight Per each | 595 |

### Uses, Certifications, and Standards

|             |   |
|-------------|---|
| Application | Mainly used for controlling 3-phase motors, non-inductive or slightly inductive loads |
| standard    | CB, CCC, cUL, CE, DNV, RINA, RoHS   |