



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

3737 Grader Street Suite 120
75041-0000, TX Garland
Phone: 214-503-7227
Fax: 214-503-9766



AF30301113 AF30-30-11-13 100-250V50

Industrial Connections &

Catalog Number	AF30301113
Manufacturer	Industrial Connections &
Description	AF30 Contactors Are Used For Controlling Power Circuits Up to 690 V Ac and 220 V DC. They Are Mainly Used For Controlling 3-Phase Motors, Non-Inductive or Slightly Inductive Loads. Af... Contactors Include An Electronic Coil Interface Accepting A Wide Control Voltage Uc Min. ... Uc Max. Only Four Coils Cover Control Voltages Between 24...500 V 50/60 HZ or 20...500 V DC. Af Contactors Can Manage Large Control Voltage Variations. One Coil Can Be Used For Different Control Voltages Used Worldwide Without Any
Weight per unit	0.8500 (lbs/each)
Product Category	IEC Contactors

Descriptions

Description	AF30-30-11-13 100-250V50
extra long description	ABB AF30-30-11-13 AF30-30-11-13 100
Long Description	AF30 contactors are used for controlling power circuits up to 690 V AC and 220 V DC. They are mainly used for controlling 3-phase motors, non-inductive or slightly inductive loads. AF... contactors include an electronic coil interface accepting a wide control voltage Uc min. ... Uc max. Only four coils cover control voltages between 24...500 V 50/60 Hz or 20...500 V DC. AF contactors can manage large control voltage variations. One coil can be used for different control voltages used worldwide without any
Product Type	AF30-30-11-13 100-250V50/60HZ-DC CO

Manufacturer Information

Brand	ABB
GTIN	00888614244276
Manufacturers Part Number	AF30-30-11-13
UPC	888614244276

Taxonomies, Classifications, and Categories

Category Description	IEC/FREEDOM CONTACTOR
----------------------	-----------------------

Packaging

Carton	1
Weight Per each	0.85