



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

5510 West 65th Street
72209-0000, AR Little Rock
Phone: 501-565-1785
Fax: 501-565-0827



AF52301114 54A, 250-500V, 3P Contactor

Industrial Connections &

Catalog Number	AF52301114
Manufacturer	Industrial Connections &
Description	AF52 Contactors Are Used For Controlling Power Circuits Up to 690 V Ac and 220 V DC. They Are Mainly Used For Controlling 3-Phase Motors, Non-Inductive or Slightly Inductive Loads. Af... Contactors Include An Electronic Coil Interface Accepting A Wide Control Voltage Uc Min. ... Uc Max. Only Four Coils Cover Control Voltages Between 24...500 V 50/60 HZ or 20...500 V DC. Af Contactors Can Manage Large Control Voltage Variations. One Coil Can Be Used For Different Control Voltages Used Worldwide Without Any
Weight per unit	2.4 (lbs/each)
Product Category	IEC Contactors

Descriptions

Description	54A, 250-500V, 3P CONTACTOR
extra long description	ABB AF52-30-11-14 CTR,3P,54A,250-50
Long Description	AF52 contactors are used for controlling power circuits up to 690 V AC and 220 V DC. They are mainly used for controlling 3-phase motors, non-inductive or slightly inductive loads. AF... contactors include an electronic coil interface accepting a wide control voltage Uc min. ... Uc max. Only four coils cover control voltages between 24...500 V 50/60 Hz or 20...500 V DC. AF contactors can manage large control voltage variations. One coil can be used for different control voltages used worldwide without any
Product Type	CTR, 3P, 54A, 250-500VAC/DC, 2/2

Manufacturer Information

Brand	ABB
GTIN	00888614119871
Manufacturers Part Number	AF52-30-11-14
UPC	888614119871

Taxonomies, Classifications, and Categories

Category Description	IEC/FREEDOM CONTACTOR
----------------------	-----------------------

Packaging

Carton	1
Weight Per each	2.3899