



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

1612 E. Booth Road
72143-0000, AR Searcy
Phone: 501-368-0309
Fax: 501-368-0619



AF96301114 92A, 250-500V, 3P Contactor

Industrial Connections &

Catalog Number	AF96301114
Manufacturer	Industrial Connections &
Description	AF96 Contactors Are Used For Controlling Power Circuits Up to 690 V Ac and 220 V DC. They Are Mainly Used For Controlling 3-Phase Motors, Non-Inductive or Slightly Inductive Loads. Af... Contactors Include An Electronic Coil Interface Accepting A Wide Control Voltage Uc Min. ... Uc Max. Only Four Coils Cover Control Voltages Between 24...500 V 50/60 HZ or 20...500 V DC. Af Contactors Can Manage Large Control Voltage Variations. One Coil Can Be Used For Different Control Voltages Used Worldwide Without Any
Weight per unit	3.0 (lbs/each)
Product Category	IEC Contactors

Descriptions

Description	92A, 250-500V, 3P CONTACTOR
extra long description	ABB AF96-30-11-14 CTR,3P,92A,250-50
Long Description	AF96 contactors are used for controlling power circuits up to 690 V AC and 220 V DC. They are mainly used for controlling 3-phase motors, non-inductive or slightly inductive loads. AF... contactors include an electronic coil interface accepting a wide control voltage Uc min. ... Uc max. Only four coils cover control voltages between 24...500 V 50/60 Hz or 20...500 V DC. AF contactors can manage large control voltage variations. One coil can be used for different control voltages used worldwide without any
Product Type	CTR, 3P, 92A, 250-500VAC/DC, 1/1

Manufacturer Information

Brand	ABB
GTIN	00888614131606
Manufacturers Part Number	AF96-30-11-14
UPC	888614131606

Taxonomies, Classifications, and Categories

Category Description	IEC/FREEDOM CONTACTOR
----------------------	-----------------------

Packaging

Carton	1
Package	54
Weight Per each	2.96