



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

700 York Ave.
67401-0000, KS Salina
Phone: 785-914-5431
Fax: 785-914-5432



AHDS60SSR 60A Disconnect Switch

Eaton Wiring Devices

Catalog Number	AHDS60SSR
Manufacturer	Eaton Wiring Devices
Description	Eaton Motor Control Disconnect X-Switch, IP69K, IP66 Ingress, #14-4 Awg, 60A, Mounting Feet/Din Rail, Flush or 1/4" Spacing, 600V, Gray, Nema 4X, 12, Enclosure: 316L SS, Washdown, Three-Phase, Rotary, NSF Certified For Food Processing
Weight per unit	8.7 (lbs/each)
Product Category	Disconnect Motor Switches

Features

amperage rating	60A
dimensions	9.0000 IN X 6.5000 IN X 17.5000 IN
Poles	Three-pole
Voltage Rating	600 V

Descriptions

Description	60A DISCONNECT SWITCH
extra long description	EWD AHDS60SSR Disconnect Switch, 60
Features	Additionally, our non-fused motor control disconnect switch and our new stainless-steel X-Switch are NSF listed for use in food processing. Offering flexible and economical designs for both fused and non-fused applications, Eaton's Arrow Hart motor control disconnect switches are built for use in harsh industrial applications to address the needs of safety, reduced downtime and code compliance. Our industrial grade, electrical motor controls feature durable lever handles and switch mechanisms that will wit
Long Description	Eaton motor control disconnect X-switch, IP69K, IP66 Ingress, #14-4 AWG, 60A, Mounting feet/DIN rail, flush or 1/4" spacing, 600V, Gray, NEMA 4X, 12, Enclosure: 316L SS, Washdown, Three-phase, Rotary, NSF certified for food processing
Product Type	Disconnect Switch, 60a
Special Features	IP69K, IP66 Ingress Protection Ratings

Manufacturer Information

Brand	Eaton Wiring Devices
GTIN	00032664755316
Manufacturers Part Number	AHDS60SSR
UPC	032664755316



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

700 York Ave.
67401-0000, KS Salina
Phone: 785-914-5431
Fax: 785-914-5432

Taxonomies, Classifications, and Categories

Category Description	Residential Switches
Type	Motor control disconnect X-switch

Packaging

Carton	1
Weight Per each	8.7

Uses, Certifications, and Standards

Application	Ind Facilities & Factories - Facility - Other
environmental conditions	WashdownFood processingComplex
nema rating	124X
standard	NSF Listed