



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

1011 First Place Blvd
73099-0000, OK Yukon
Phone: 405-265-8424
Fax: 405-494-4041



B41 B-Cap Wire Connector, Model B4 Blue/Gray, 25/Box

Ideal

Catalog Number	B41
Manufacturer	Ideal
Description	Color: Blue/Gray, Buchanan, Wire Connector, B-Cap®;, Conductor Range: 14 - 6 Awg, 2/12 Awg Min, 2/6 Awg Max, Number Of Conductors: 2 to 6, Material: Flame-Retardant Polypropelene, Voltage Rating: 600 V, Environmental Conditions: Tough, UI 94V-2 Flame-Retardant Shell Rated At 105 Deg C (221 F), Model Number: B4
Weight per unit	0.0180 (lbs/each)
Product Category	Electrical Fixture Conn (Nuts

Features

Material	Flame-retardant Polypropelene
Voltage Rating	600

Material, Color, and Finish

Color	Blue/Gray
-------	-----------

Descriptions

Description	B-CAP WIRE CONNECTOR, MODEL B4 BLUE/GRAY, 25/BOX
extra long description	IDEAL B4-1 B-CAP B4 BLUE GRAY, 25 B

Features
The B-CAP Wire Connector gets you in those hard-to reach spots comfortably, especially when you're retrofitting or updating. Slim, classic fins and an expanding interior spring give the B-CAP a secure grip with extra leverage, making it the most compact connector on the market for up to 5 #12 (Red Model B2).The unique, space-saving profile of the B-CAP makes it perfect for retrofit work and shallow boxes.The B-CAP also features a tough, flame-retardant shell that withstands environmental extremes with a de

Long Description	Color: Blue/Gray, Buchanan, Wire Connector, B-CAP®;, Conductor Range: 14 - 6 AWG, 2/12 AWG Min, 2/6 AWG Max, Number Of Conductors: 2 to 6, Material: Flame-retardant Polypropelene, Voltage Rating: 600 V, Environmental Conditions: Tough, UL 94V-2 Flame-Retardant Shell Rated At 105 DEG C (221 F), Model Number: B4
------------------	--

Manufacturer Information

Brand	Buchanan
GTIN	00781789452036
UPC	781789452036



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

1011 First Place Blvd
73099-0000, OK Yukon
Phone: 405-265-8424
Fax: 405-494-4041

Taxonomies, Classifications, and Categories

Category Description Datacom Wiring Devices and Accessories

Availability

minimum qty 25

Status Inactive

Packaging

Carton 250

Weight Per each 0.018

Uses, Certifications, and Standards

Application Insulating or Joining 1 or more conductors

environmental conditions Tough, UL 94V-2 Flame-Retardant Shell Rated At 105 DEG C (221 F)

standard CSA C22.2 #188, UL 486C Listed, RoHS