



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

5510 West 65th Street
72209-0000, AR Little Rock
Phone: 501-565-1785
Fax: 501-565-0827

C1.5WH6 1-1/2X72" NM WHT Duct CVR

Panduit Corporation

Catalog Number	C1.5WH6
Manufacturer	Panduit Corporation
Description	The C1.5WH6 PVC Flush Wiring Duct Cover Features A Non-Slip, Liner to Prevent Cover Slide. Designed With The User In Mind, The Cover Is Easy to Install and Remove. The General-Purpose Lead-Free PVC Material Is Suitable For Use In Indoor Applications. UI 94 Flame Class Of V-0 With A UI Recognized Continuous-Use Temperature Up to 122°F (50°C). 0.35" X 1.75" (8.9 MM X 44.5 MM) and 6' (1.83 M) Long. Color White.
Weight per unit	0.0880 (lbs/each)
Product Category	Ducts, Raceways, Runways, Tray

Features

connection	Snap-on
media	Yes

Material, Color, and Finish

Color	White
-------	-------

Dimensions and Weight

Length	NA
Width	1.75

Descriptions

Description	1-1/2X72" NM WHT DUCT CVR
extra long description	PAN C1.5WH6 Panduct® C1.5WH6 Flush
Long Description	The C1.5WH6 PVC Flush Wiring Duct Cover features a non-slip, liner to prevent cover slide. Designed with the user in mind, the cover is easy to install and remove. The general-purpose lead-free PVC material is suitable for use in indoor applications. UL 94 flame class of V-0 with a UL recognized continuous-use temperature up to 122°F (50°C). 0.35" x 1.75" (8.9 mm x 44.5 mm) and 6' (1.83 m) long. Color White.
Product Type	Panduct® C1.5WH6 Flush Duct Cover

Manufacturer Information

Brand	PANDUIT
GTIN	00074983230624
Manufacturers Part Number	C1.5WH6
UPC	074983230624



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

5510 West 65th Street
72209-0000, AR Little Rock
Phone: 501-565-1785
Fax: 501-565-0827

Taxonomies, Classifications, and Categories

Category Description	Panduit & Wiremold Metallic & Non-Metallic Raceways
Type	Flushed Duct Cover

Availability

minimum qty	6
-------------	---

Packaging

Carton	6
Package	120
Weight Per foot	0.088

Uses, Certifications, and Standards

Application	Cover for Wiring Duct
standard	CE Compliant;CSA Certified;Flammability Ratings: UL94 V-0;RoHS Compliant;UL Recognized