



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

802 West Main
75652-4459, TX Henderson
Phone: 903-657-1517
Fax: 903-657-0253



CG410 CG Mle Straight 1/2 .560-.625

Pass & Seymour/Legrand

Catalog Number	CG410
Manufacturer	Pass & Seymour/Legrand
Description	Cord Grip Male Straight, 1/2-Inch NPT, 0.500-Inch-0.625-Inch
Weight per unit	0.1160 (lbs/each)
Product Category	Cable & Cord Grips

Features

Cable Size	NPT Size: 1/2; Cable Dia. Range: 0.560-0.625
Cable Type	Various Types of Electrical Conductor/Cable
indoor/outdoor load	Both Strain Relief Grips are designed to prevent tension from being transferred to junctions and terminals on electrical cord, cable and conduit, therefore providing a more secure electrical structure.
Material	Aluminum

Descriptions

Construction	Various Types of Pulling, Support and Strain Relief Grips
Description	CG MLE STRAIGHT 1/2 .560-.625
extra long description	P&S CG410 CG MLE STR 1/2 .560-.625
Features	Cord Grip Male Straight, 1/2-inch NPT, 0.500-inch-0.625-inch
Long Description	Cord Grip Male Straight, 1/2-inch NPT, 0.500-inch-0.625-inch
Product Type	CG Mle STR 1/2 .560-.625
Special Features	Deluxe cord grips are woven of stainless steel mesh with an aluminum body for corrosion resistance. They are offered in single/double weave construction to help absorb direct pull, to resist flexing and binding, and to eliminate strain. They are recommended for indoor or outdoor use where subjected to moisture in the wiring of pendant stations, processing equipment, hand tools, and extension cord sets. Deluxe grips are suitable for use in hazardous locations per Class I, Div. 2: Class II, Div. 1 & 2: and C

Manufacturer Information

Brand	Pass and Seymour
GTIN	00785007996494
Manufacturers Part Number	CG410
UPC	785007996494

Taxonomies, Classifications, and Categories

Category Description	CORD CONNECTORS & CORD GRIPS
Type	Cord grip



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

802 West Main
75652-4459, TX Henderson
Phone: 903-657-1517
Fax: 903-657-0253

Packaging

Carton	1
Package	20
Weight Per each	0.116

Uses, Certifications, and Standards

Application	Industrial
Capacity	Various Cable Diameter Ranges
Mounting standard	Consult the Factory for Mounting Recommendations UL, CSA, UL/CSA Approval (consult factory)