



# ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.  
75964-0000, TX Nacogdoches  
Phone: 936-569-7941  
Fax: 936-560-4685



## CR20 Duplex Recp 20A 125V Side Wire BR

*Pass & Seymour/Legrand*

|                  |                                                                                                                                                                                                                                                           |
|------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Catalog Number   | CR20                                                                                                                                                                                                                                                      |
| Manufacturer     | Pass & Seymour/Legrand                                                                                                                                                                                                                                    |
| Description      | Duplex Receptacle, 20 A, 125 V, 2 Poles, 3 Wires, #14 to #10 Awg<br>Compatible Wire Size, Side Wire Connection, Wall Mount, 1.322<br>In Length, 0.78 In Width, 3.281 In Height, Thermoplastic, Brown,<br>Impact Resistant, Corrosion Resistant, 0.2000 LB |
| Weight per unit  | 0.1962 (lbs/each)                                                                                                                                                                                                                                         |
| Product Category | Gen Purpose Recept & Surge Pro                                                                                                                                                                                                                            |

### Features

|                     |                |
|---------------------|----------------|
| amperage rating     | 20             |
| connection          | Wire Ground    |
| indoor/outdoor      | Indoor         |
| Outlet Type         | STRAIGHT BLADE |
| Poles               | 2              |
| Voltage             | 125.0 V        |
| Voltage Rating      | 125            |
| Wall Plate Included | NO             |
| Wire Size           | 14 - 10        |

### Material, Color, and Finish

|        |       |
|--------|-------|
| Finish | Matte |
|--------|-------|

### Dimensions and Weight

|      |        |
|------|--------|
| Size | 3.3 in |
|------|--------|

### Descriptions

|                        |                                     |
|------------------------|-------------------------------------|
| Description            | RECEP DUP 20A/125V SIDE WIRE BROWN  |
| extra long description | P&S CR20 RECEP DUP 20A/125V SIDE WI |

### Manufacturer Information

|       |                  |
|-------|------------------|
| Brand | Pass and Seymour |
| GTIN  | 00785007119121   |
| UPC   | 785007119121     |

### Taxonomies, Classifications, and Categories

|                      |                        |
|----------------------|------------------------|
| Category Description | Commercial receptacles |
| Type                 | Outlet                 |

### Trade Size

|          |      |
|----------|------|
| Amperage | 20.0 |
|----------|------|



# ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.  
75964-0000, TX Nacogdoches  
Phone: 936-569-7941  
Fax: 936-560-4685

## Packaging

|                 |        |
|-----------------|--------|
| Carton          | 1      |
| Package         | 100    |
| Weight Per each | 0.1962 |

## Uses, Certifications, and Standards

|                       |               |
|-----------------------|---------------|
| Mounting              | WALL          |
| Operating Temperature | -40°-60°C     |
| standard              | CULUS, UL 498 |