



# ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.  
75964-0000, TX Nacogdoches  
Phone: 936-569-7941  
Fax: 936-560-4685



## CS20AC3I 20A 120/277VAC S Wire Comm 3W SW Iv

Pass & Seymour/Legrand

|                  |                                                                                                                                                                                                                                                                |
|------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Catalog Number   | CS20AC3I                                                                                                                                                                                                                                                       |
| Manufacturer     | Pass & Seymour/Legrand                                                                                                                                                                                                                                         |
| Description      | Toggle Switch, 3 Poles, 3 Ways, 20 A, 120/277 V Ac, Nylon Material, Silver Cadmium Oxide Contact Material, Ivory, Grounding Connection, Wall Mount, 1.320 (L) X 1.073 (W) X 3.281 (H) In, -40 °C Operating Temperature, +115 °C Operating Temperature, 0.18 LB |
| Weight per unit  | 0.1820 (lbs/each)                                                                                                                                                                                                                                              |
| Product Category | Gen Purpose Switches                                                                                                                                                                                                                                           |

### Features

|                       |                                                                |
|-----------------------|----------------------------------------------------------------|
| action                | Three pole                                                     |
| actuator              | Toggle                                                         |
| amperage rating       | 20                                                             |
| connection            | Side Wire or external screw-pressure plate                     |
| Contact Configuration | One piece brass alloy contact arm                              |
| Contact Rating        | Oversized silver alloy contacts                                |
| Degree of Protection  | 1500V Dielectric Withstand Voltage                             |
| indoor/outdoor        | Indoor                                                         |
| insulation            | False                                                          |
| Load Rating           | 20 A @ 120/277 VAC                                             |
| Load Type             | Fluorescent, LED, Xenon, Universal, Incandescent, CFL, Halogen |
| media                 | Yes                                                            |
| Number of Gangs       | 1                                                              |
| Number of Switches    | 1.0                                                            |
| Poles                 | 3-way                                                          |
| Switch Type           | Toggle                                                         |
| throw type            | Double Throw                                                   |
| Voltage               | 120 VAC, 277 VAC                                               |
| Wall Plate Included   | NO                                                             |
| Wire Size             | #14 - #10 Awg                                                  |

### Material, Color, and Finish

|        |       |
|--------|-------|
| Finish | Matte |
|--------|-------|

### Dimensions and Weight

|      |        |
|------|--------|
| Size | 3.3 in |
|------|--------|

### Descriptions

|                        |                                    |
|------------------------|------------------------------------|
| Description            | 20A 120/277VAC S WIRE COMM 3W SW I |
| extra long description | P&S CS20AC3I 20A 120/277VAC S WIRE |



# ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.  
75964-0000, TX Nacogdoches  
Phone: 936-569-7941  
Fax: 936-560-4685

## Manufacturer Information

|                           |                  |
|---------------------------|------------------|
| Brand                     | Pass and Seymour |
| GTIN                      | 00785007126532   |
| Manufacturers Part Number | CS20AC3I         |
| UPC                       | 785007126532     |

## Taxonomies, Classifications, and Categories

|                      |                     |
|----------------------|---------------------|
| Category Description | Commercial switches |
| Type                 | SWITCH              |

## Trade Size

|          |      |
|----------|------|
| Amperage | 20.0 |
|----------|------|

## Packaging

|                 |       |
|-----------------|-------|
| Carton          | 1     |
| Package         | 50    |
| Weight Per each | 0.182 |

## Uses, Certifications, and Standards

|                                   |                                                                                                               |
|-----------------------------------|---------------------------------------------------------------------------------------------------------------|
| Application                       | Commercial                                                                                                    |
| Enclosure                         | Nylon                                                                                                         |
| Mounting                          | WALL                                                                                                          |
| Operating Temperature<br>standard | -40°-115°F<br>CULUS, UL Listed E140597, Standard UL20, FedSpec WS896,<br>Flammability Rating UL94 V2, FEDSPEC |