



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

537 N 40th St
72762-0000, AR Springdale
Phone: 479-361-2266
Fax: 479-361-9188



DE713 3/0-4 Cu Solderless Lug

Nsi Industries

Catalog Number	DE713
Manufacturer	Nsi Industries
Description	Copper Solderless Lug, 3/0-4 Awg With 3/8" Mounting Hole Is Made Of 99.98 Pure Electrolytic Copper. Steel-Plated Screws to Prevent Rusting. 25 to 70 Ampere Size and Has 3/8" Hex Head Screws. Rated 600 Volts Max. UI 486 Listed. Temperature Rating 90 Degrees C.
Weight per unit	0.1700 (lbs/each)
Product Category	Large Terminals & Connectors

Features

amperage rating	175
Cable Size	3/0-4 AWG
Material	Copper
Number of Holes	1
Voltage Rating	600 V
Warranty	1 YEAR

Material, Color, and Finish

Color	Copper
-------	--------

Dimensions and Weight

Size	L=2.190 - H=1.030 - W=.750
------	----------------------------

Descriptions

Description	3/0-4 CU SOLDERLESS LUG
extra long description	NSI DE713 Solderless Lug 3/0-4 Copp
Features	Copper Solderless Lug 3/0 - 4 AWG: Made of 99.98 pure electrolytic copper. Steel-plated screws to prevent rusting. 25 to 70 ampere size have slotted head screws. Larger sizes have hex head screws. Rated 600 volts max. UL 486 Listed. Temperature rating 90 degrees C.
Long Description	Copper Solderless Lug, 3/0-4 AWG with 3/8" Mounting Hole is made of 99.98 pure electrolytic copper. Steel-plated screws to prevent rusting. 25 to 70 ampere size and has 3/8" hex head screws. Rated 600 volts max. UL 486 Listed. Temperature rating 90 degrees C.
Product Type	Solderless Lug 3/0-4 Copper
Special Features	3/0-4 AWG - CU Only - 18 Pack



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

537 N 40th St
72762-0000, AR Springdale
Phone: 479-361-2266
Fax: 479-361-9188

Manufacturer Information

Brand	Polaris
GTIN	00662381005151
Manufacturers Part Number	DE713
UPC	662381005151

Taxonomies, Classifications, and Categories

Category Description	Comp & Mech Lugs and Butt Splices
Type	Copper Single Lug

Packaging

Carton	1
Package	18
Weight Per each	0.17

Uses, Certifications, and Standards

Application	NSI
environmental conditions	90 C
standard	UL486A