



# ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

201 South Persimmon Street  
77375-6855, TX Tomball  
Phone: 281-357-5300  
Fax: 281-357-5005



## F3X4LG6 3" X 4" Slotted Wiring Duct, Light Gray Panduit Corporation

Catalog Number	F3X4LG6
Manufacturer	Panduit Corporation
Description	The F3X4LG6 Panduct Lead-Free PVC Narrow Slot Wiring Duct Features A Narrow Slot/Finger Design That Closely Matches The Spacing Of High-Density Components. Upper and Lower Scorelines Allow For Easy Finger/Sidewall Section Removal. UI 94 Flame Class Of V-0 With A UI Recognized Continuous-Use Temperature Up to 122°F (50°C). Mounting Holes Provided. Lead-Free PVC. 3" X 4" (76.2 MM X 101.6 MM) and 6' (1.83 M) Long. Cover Sold Separately. Color Light Gray.
Weight per unit	0.5780 (lbs/each)
Product Category	Ducts, Raceways, Runways, Tray

### Features

connection	Mounting Holes
media	Yes

### Material, Color, and Finish

Color	Gray
-------	------

### Dimensions and Weight

Height	4.10
Length	NA
Size	3.00 x 4.00
Width	3.25

### Descriptions

Description	3" X 4" SLOTTED WIRING DUCT, LIGHT GRAY
extra long description	PAN F3X4LG6 Panduct® F3X4LG6 Base W
Long Description	The F3X4LG6 Panduct Lead-Free PVC Narrow Slot Wiring Duct features a narrow slot/finger design that closely matches the spacing of high-density components. Upper and lower scorelines allow for easy finger/sidewall section removal. UL 94 flame class of V-0 with a UL recognized continuous-use temperature up to 122°F (50°C). Mounting holes provided. Lead-free PVC. 3" x 4" (76.2 mm x 101.6 mm) and 6' (1.83 m) long. Cover sold separately. Color Light Gray.
Product Type	Panduct® F3X4LG6 Base Wiring Duct



# ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

201 South Persimmon Street  
77375-6855, TX Tomball  
Phone: 281-357-5300  
Fax: 281-357-5005

## Manufacturer Information

Brand	PANDUIT
GTIN	00074983375813
Manufacturers Part Number	F3X4LG6-A
UPC	074983375813

## Taxonomies, Classifications, and Categories

Category Description	WIRE DUCT AND COVERS
Type	Base Wiring Duct

## Availability

minimum qty	6
-------------	---

## Packaging

Carton	6
Package	60
Weight Per foot	0.578

## Uses, Certifications, and Standards

Application	Narrow slot/finger design provides more slots to fit the spacing of high-density terminal block applications
standard	RoHS Compliant, UL Recognized, CE Compliant, BABA Compliant