



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

3101 Industrial Terrace
78758-0000, TX Austin
Phone: 512-351-3290
Fax: 512-973-9027



F48T12DH0 60W T12 48" Daylight High Output 76 Cri R17D

Ge By Current Lamps

| | |
|------------------|---|
| Catalog Number | F48T12DH0 |
| Manufacturer | Ge By Current Lamps |
| Description | Ge, 60 WTT, 3400 LM, 6500 KV, 75 Cri, 1.5 In Diameter, 48 In Length, Recessed Double Contact (R17D) Base, 12000 HR Average Life |
| Weight per unit | 0.8300 (lbs/each) |
| Product Category | Linear Fluorescent Straight La |

Features

| | |
|--------------|--------------------------------|
| average life | 12000 |
| Base | Recessed Double Contact (R17d) |
| lumens | 3400 |
| Wattage | 60 |

Material, Color, and Finish

| | |
|-----------------------------|--------|
| color rendering index (cri) | 75.0 |
| color temperature | 6500.0 |

Dimensions and Weight

| | |
|----------|-----|
| Diameter | 1.5 |
| Length | 48 |

Descriptions

| | |
|------------------------|---|
| Description | 60W T12 48" DAYLIGHT HIGH OUTPUT 76 CRI R17D |
| extra long description | GEL F48T12/D/HO 10778 FLUORESCENT |
| Long Description | GE, 60 WTT, 3400 LM, 6500 KV, 75 CRI, 1.5 IN Diameter, 48 IN Length, Recessed Double Contact (R17d) Base, 12000 HR Average Life |
| Product Type | 10778 Fluorescent |

Manufacturer Information

| | |
|---------------------------|----------------------|
| Brand | Ge Traditional Lamps |
| GTIN | 00043168107785 |
| Manufacturers Part Number | F48T12/D/HO |
| UPC | 043168107785 |

Taxonomies, Classifications, and Categories

| | |
|----------------------|-------------|
| Category Description | Fluorescent |
|----------------------|-------------|

Packaging

| | |
|-----------------|------|
| Carton | 1 |
| Package | 24 |
| Weight Per each | 0.83 |



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

3101 Industrial Terrace
78758-0000, TX Austin
Phone: 512-351-3290
Fax: 512-973-9027

Uses, Certifications, and Standards

Application

Full Wattage