



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

4000 Mockingbird Ln
79109-3210, TX Amarillo
Phone: 806-220-0404
Fax: 806-220-0811



FRSR12 Fusetron Dual Element Fus

Bussmann Fuses

Catalog Number	FRSR12
Manufacturer	Bussmann Fuses
Description	Eaton Bussmann Series Class RK5 Fuse, FRS-R, Time-Delay, Dual-Element, Current Limiting Fuse, 12 A, Non-Indicating Fuse, Interrupting Rating Of 200 Ka At 600 Vac and 20 Ka At 300 VDC
Weight per unit	1.3 (lbs/each)
Product Category	Dual Element

Features

amperage rating	12
connection	Ferrule End X Ferrule End
dimensions	5.0000 IN X 0.8100 IN X 0.8100 IN
element	Dual
Fuse Class	Class RK5
interrupt rating	200 kAIC at 600 Vac 20 kAIC at 300 Vdc
media	Yes
Response Time	10 S at 500%
Voltage Rating	600 Vac, 300 Vdc

Dimensions and Weight

Size	0.81 In Diameter X 5.00 In Length
------	-----------------------------------

Descriptions

Description	FUSETRON DUAL ELEMENT FUS
extra long description	BUSS FRS-R-12 FUSETRON DUAL ELEMENT
Features	Bussmann's UL Class RK5 Fusetron product offering provides energy efficient advanced protection with its dual-element, time-delay construction and is available with optional open fuse indication on select ratings. Available in both 250Vac and 600Vac, 200kA RMS Sym interrupting rating and sizes ranging from 0 to 600 amp. Fusetron's deliver 10 seconds (minimum) of time-delay at 500 of rated current (8 seconds for 1/10-30A sizes).
Long Description	Eaton Bussmann Series Class RK5 fuse, FRS-R, time-delay, dual-element, current limiting fuse, 12 A, non-indicating fuse, interrupting rating of 200 kA at 600 Vac and 20 kA at 300 Vdc
Product Type	Fusetron Dual Element Fuse Class RK5
Special Features	Renewable



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

4000 Mockingbird Ln
79109-3210, TX Amarillo
Phone: 806-220-0404
Fax: 806-220-0811

Manufacturer Information

Brand	Eaton Bussmann series
GTIN	00051712508292
Manufacturers Part Number	FRS-R-12
UPC	051712508292

Taxonomies, Classifications, and Categories

Type	FUSE
------	------

Packaging

Carton	10
Weight Per each	1.3

Uses, Certifications, and Standards

Application	Ind Facilities & Factories - Facility: Safety and Security Systems
standard	CE Marked