



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

5510 West 65th Street
72209-0000, AR Little Rock
Phone: 501-565-1785
Fax: 501-565-0827



FST250KIT 8.5OZ Foam Duct Sealant Kit 6PK

American Polywater

Catalog Number	FST250KIT
Manufacturer	American Polywater
Description	Same As Kit Above In A Box Of 6. Protects Conduit and Raceway Systemsfst™ Closed-Cell Sealant Provides Superior Pressure-Blocking In The Toughest Environments. It Stops Water, Methane, and Other Gases to Keep Electrical Systems Intact. FST Duct Sealant Is Durable and Easy to Install. FST Is Chemically Resistant and Has Excellent Adhesion to Conduits.
Weight per unit	1.8 (lbs/each)
Product Category	Paint, Chemicals, Etc.

Features

specific gravity	1.22 @25° C
Temperature Range	-20°F - 200°F

Material, Color, and Finish

Color	Brown liquid, tan foam
-------	------------------------

Dimensions and Weight

Size	8.5
------	-----

Descriptions

Description	8.5OZ FOAM DUCT SEALANT KIT 6PK
extra long description	PWTR FST-250KIT 8.5-Oz Foam Duct Se
Long Description	Same as kit above in a box of 6. Protects Conduit and Raceway SystemsFST™ closed-cell sealant provides superior pressure-blocking in the toughest environments. It stops water, methane, and other gases to keep electrical systems intact. FST Duct Sealant is durable and easy to install. FST is chemically resistant and has excellent adhesion to conduits.
Product Type	8.5-Oz Foam Duct Sealant Kit Bulk 6-Pack
Special Features	duct sealant, reenterable, closed cell, water block, durable, easy install,

Manufacturer Information

Brand	AMERICAN POLYWATER
GTIN	00027868045714
Manufacturers Part Number	FST-250KIT
UPC	027868045714

Taxonomies, Classifications, and Categories

Category Description	ADHESIVES
Type	Foam Duct Sealant



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

5510 West 65th Street
72209-0000, AR Little Rock
Phone: 501-565-1785
Fax: 501-565-0827

Packaging

Carton	6
Weight Per each	1.8333

Uses, Certifications, and Standards

Application	closed-cell duct sealant prviding superior pressure-blocking power
standard	NEC Article 225.27, 230.8, 300.5, 300.7, 501.15; TIA-758-B standard 5.1.1.2.8,5.4.2.3, 7.4.2.8.1; UL 94, IEEE1210,