



# ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

1201 West Broadway  
79714-0000, TX Andrews  
Phone: 432-523-2423  
Fax: 432-523-2428



## GL4038 4/0 1-Hole Compression Lug 3/8" Bolt

*Nsi Industries*

|                  |                                                                                                                                                                                                                                                                                                                                                                                                  |
|------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Catalog Number   | GL4038                                                                                                                                                                                                                                                                                                                                                                                           |
| Manufacturer     | Nsi Industries                                                                                                                                                                                                                                                                                                                                                                                   |
| Description      | 1 Holeshort Barrel Copper Compression Lug W/ PEEPHOLE4/0 Awg-3/8" Bolt Short Barrel Copper Compression Lugs With Peepholeis A Type Of Copper Compression Connector That Is Produced From High Conductivity Copper Tubing. They Are Tin-Plated to Provide Corrosion Resistance and Are Marked With Die Index and Color Coded For Easy Reference. Listed For 35KV Maximum When Properly Installed. |
| Weight per unit  | 0.0800 (lbs/each)                                                                                                                                                                                                                                                                                                                                                                                |
| Product Category | Large Terminals & Connectors                                                                                                                                                                                                                                                                                                                                                                     |

### Features

|                 |               |
|-----------------|---------------|
| Cable Size      | 4/0 AWG (STR) |
| Material        | Copper        |
| Number of Holes | 1             |
| Stud Size       | 3/8           |
| Voltage Rating  | 600 V         |
| Warranty        | 1 YEAR        |

### Material, Color, and Finish

|        |            |
|--------|------------|
| Color  | Purple     |
| Finish | Tin Plated |

### Dimensions and Weight

|      |                                     |
|------|-------------------------------------|
| Size | L=2.36 - W=1.00 - OD=.690 - ID=.550 |
|------|-------------------------------------|



# ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

1201 West Broadway  
79714-0000, TX Andrews  
Phone: 432-523-2423  
Fax: 432-523-2428

## Descriptions

|                        |                                                                                                                                                                                                                                                                                                                                                                                                     |
|------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Description            | 4/0 1-HOLE COMPRESSION LUG 3/8" BOLT                                                                                                                                                                                                                                                                                                                                                                |
| extra long description | NSI GL4038 CMP Lug Cu Short 4/0 AWG                                                                                                                                                                                                                                                                                                                                                                 |
| Features               | 1 Hole Short Barrel Copper Compression Lug w/ PeepHole4/0 AWG-3/8" Bolt Short Barrel Copper Compression Lugs with Peep Hole is a type of copper compression connector that is produced from high conductivity copper tubing. They are tin-plated to provide corrosion resistance and are marked with die index and color coded for easy reference. Listed for 35KV maximum when properly installed. |
| Long Description       | 1 HoleShort Barrel Copper Compression Lug w/ PeepHole4/0 AWG-3/8" Bolt Short Barrel Copper Compression Lugs with PeepHoleis a type of copper compression connector that is produced from high conductivity copper tubing. They are tin-plated to provide corrosion resistance and are marked with die index and color coded for easy reference. Listed for 35KV maximum when properly installed.    |
| Product Type           | CMP Lug Cu Short 4/0 Awg 3/8 Bolt                                                                                                                                                                                                                                                                                                                                                                   |
| Special Features       | 4/0 AWG (STR) - 3/8 Mounting Hole                                                                                                                                                                                                                                                                                                                                                                   |

## Manufacturer Information

|                           |                |
|---------------------------|----------------|
| Brand                     | Polaris        |
| GTIN                      | 00662381036377 |
| Manufacturers Part Number | GL4038         |
| UPC                       | 662381036377   |

## Taxonomies, Classifications, and Categories

|                      |                                   |
|----------------------|-----------------------------------|
| Category Description | Comp & Mech Lugs and Butt Splices |
| Type                 | Short Barrel - One Hole           |

## Packaging

|                 |      |
|-----------------|------|
| Carton          | 1    |
| Package         | 25   |
| Weight Per each | 0.08 |

## Uses, Certifications, and Standards

|                          |                                         |
|--------------------------|-----------------------------------------|
| Application              | Terminate, Splice, Tap Power Connectors |
| environmental conditions | 90 C                                    |
| Mounting                 | 3/8 Mountign Hole                       |
| standard                 | UL486A/B                                |