



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

711 Lake Bardwell Dr.
75119-0000, TX Ennis
Phone: 972-875-3413
Fax: 972-875-3174



GPD19BR 19.5 BRZ NM WP Low-Profile Gard'N Post *Arlington Industries*

Catalog Number	GPD19BR
Manufacturer	Arlington Industries
Description	Gard-N-Post. 19.5" Support For Gfci Devices Outdoors. Built In Stabilizers For Extra Stability. Openings In Stabilizers Allow For Insertion Of Extra Support Material. Angle Cut Post For Easy Access To Underground Wiring. Two 1/2" Knockouts. Color Brown. Color Is Permanent, No Chipping. Clear Extra Duty Weatherproof In Use Cover Installed.
Weight per unit	2.0 (lbs/each)
Product Category	Lighting Accessories

Features

Fixture Type	GFCI Device
Material	Plastic

Material, Color, and Finish

Color	Bronze
-------	--------

Dimensions and Weight

Size	L(19.500) x W(6.269) x H(2.964)
------	---------------------------------

Descriptions

Description	19.5 BRZ NM WP LOW-PROFILE GARD'N POST
extra long description	ARL GPD19BR POST W/IN USE COVER BR
Long Description	Gard-N-Post. 19.5" support for GFCI devices outdoors. Built in stabilizers for extra stability. Openings in stabilizers allow for insertion of extra support material. Angle Cut post for easy access to underground wiring. Two 1/2" Knockouts. Color Brown. Color is permanent, no chipping. Clear extra duty weatherproof in use cover installed.
Product Type	Post W/In Use Cover BR
Special Features	Includes Built In Weatherproof Cover

Manufacturer Information

Brand	ARLINGTON
GTIN	00018997770219
Manufacturers Part Number	GPD19BR
UPC	018997770219

Taxonomies, Classifications, and Categories

Category Description	Poles & Accessories
Type	Low Profile Enclosure



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

711 Lake Bardwell Dr.
75119-0000, TX Ennis
Phone: 972-875-3413
Fax: 972-875-3174

Packaging

Carton	1
Package	6
Weight Per each	1.98

Uses, Certifications, and Standards

Application	Outdoor, GFCI Device
Mounting	POST
standard	UL and CSA