



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

1550 Wilson Rd.
77338-0000, TX Humble
Phone: 281-548-0169
Fax: 281-548-0198



GUAL14SA 1/2" Gual Alu Conduit Outlet Box

Crouse-Hinds

Catalog Number	GUAL14SA
Manufacturer	Crouse-Hinds
Description	Eaton Crouse-Hinds Series Condulet Gua Conduit Outlet Box With Cover, 2" Cover Opening Diameter, Copper-Free Aluminum, L Shape, 1/2"
Weight per unit	0.8000 (lbs/each)
Product Category	Alum

Features

dimensions	3.3800 IN X 2.2500 IN X 3.3800 IN
------------	-----------------------------------

Descriptions

Construction	Explosionproof, Dust-Ignitionproof, Raintight
Description	1/2" GUAL ALU CONDUIT OUTLET BOX
extra long description	CRS-H GUAL14 SA 1/2 AL OUTL BX 2 CV
Features	Crouse-Hinds series GUA and GUR explosionproof conduit outlet boxes are installed in conduit systems in hazardous areas to protect conductors in threaded rigid conduit, act as pull and splice boxes, change conduit direction, and provide access to conductors for maintenance and future system changes. GUA and GUR outlet boxes are certified for Class I, Division 1, Groups B, C, D and Class II, Division 1, Groups E, F, G. GUA boxes are available in ten different hub arrangements, maximizing flexibility in th
Long Description	Eaton Crouse-Hinds series Condulet GUA conduit outlet box with cover, 2" cover opening diameter, Copper-free aluminum, L shape, 1/2"
Product Type	1/2 Al Outl BX 2 CVR THRD Rigid/Imc

Manufacturer Information

Brand	Eaton
GTIN	00782274021126
Manufacturers Part Number	GUAL14 SA
UPC	782274021126

Taxonomies, Classifications, and Categories

Category Description	HUB STYLE BOXES (GUAB, GUAT, ETC)
Type	Conduit outlet box with cover

Packaging

Carton	2
Weight Per each	0.8



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

1550 Wilson Rd.
77338-0000, TX Humble
Phone: 281-548-0169
Fax: 281-548-0198

Uses, Certifications, and Standards

Application	Ind Facilities & Factories - Industrial Facilities/Factories - Other
standard	UL 886, CSA C22.2