



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

1500 West Cotton
75604-0000, TX Longview
Phone: 903-757-8491
Fax: 903-758-0441



HBLDS3RC Disconnect, 30A Unfused, 4X Rep Cover

Hubbell Wiring Devices

Catalog Number	HBLDS3RC
Manufacturer	Hubbell Wiring Devices
Description	Switches and Lighting Controls, Industrial Grade, Disconnect Switches, Unfused Switch, Replacement Cover For 30a
Weight per unit	0.9720 (lbs/each)
Product Category	Non-Fusible Disconnect Safety

Features

Contact Configuration	Two Position
Material	COMPOSITE
pallet quantity	350

Dimensions and Weight

Size	Standard Sized
------	----------------

Descriptions

Description	DISCONNECT, 30A UNFUSED, 4X REP COVER
extra long description	HWDK HBLDS3RC DISCONNECT, 30A UNFUS
Features	NEC section 430.102(B) requires each motor controller to have a disconnect within line of sight from the motor and driven equipment. Hubbell's Circuit-Lock® Unfused Disconnect Switches are UL listed as a manual motor controller and also "suitable as a motor disconnect" and meet these code requirements.
Long Description	Switches and Lighting Controls, Industrial Grade, Disconnect Switches, Unfused Switch, Replacement Cover for 30A
Product Type	Disconnect, 30A Unfused, 4X Rep Cover
Special Features	Standard Product

Manufacturer Information

Brand	WIRING DEVICE-KELLEMS
GTIN	00783585912448
Manufacturers Part Number	HBLDS3RC
series	Fused;Non-Fused
UPC	783585912448

Taxonomies, Classifications, and Categories

Category Description	DISCONNECTS
Type	Accessories

Packaging

Carton	1
Package	10
Weight Per each	0.972



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

1500 West Cotton
75604-0000, TX Longview
Phone: 903-757-8491
Fax: 903-758-0441

Uses, Certifications, and Standards

Application	Labelless (30A)
environmental conditions	Indoor Dry unless protected by additional means
standard	UL 746C