



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

12555 Harris Branch Pkwy Suite 105
78653-0000, TX Manor
Phone: 512-339-8750
Fax: 512-339-6732

HSTT150C 1-1/2-3/4" 100' BLK Thinwall HS Tube *Panduit Corporation*

| | |
|------------------|--|
| Catalog Number | HSTT150C |
| Manufacturer | Panduit Corporation |
| Description | The HSTT150-C Thin Wall Heat Shrink Tubing Shrinks Around Wires, Connectors, Joints, and Terminals When Heated to Protect Against Abrasion. Applications Include Insulating and Protecting Wires/Cables In Indoor, Dry Locations. Shrink Ratio: 2:1. Temperature Range: -67°F to 275°F (-55°C to 135°C). Flame Retardant, Cross-Linked Polyolefin. 1.50" Diameter X 100' Long (38.1 MM X 30.5 M). Color Black. 1 Roll. |
| Weight per unit | 6.1 (lbs/each) |
| Product Category | Insulating Materials |

Features

| | |
|------------------|-----------------|
| flammability | Flame Retardant |
| media | Yes |
| outside diameter | 1.5 |
| Shrink Ratio | 2:1 |

Material, Color, and Finish

| | |
|-------|-------|
| Color | Black |
|-------|-------|

Dimensions and Weight

| | |
|-----------|------|
| Thickness | 0.04 |
|-----------|------|

Descriptions

| | |
|------------------------|--|
| Description | 1-1/2-3/4" 100' BLK THINWALL HS TUBE |
| extra long description | PAN HSTT150-C Dry-Shrink™ HSTT150-C |
| Long Description | The HSTT150-C Thin Wall Heat Shrink Tubing shrinks around wires, connectors, joints, and terminals when heated to protect against abrasion. Applications include insulating and protecting wires/cables in indoor, dry locations. Shrink ratio: 2:1. Temperature range: -67°F to 275°F (-55°C to 135°C). Flame retardant, cross-linked polyolefin. 1.50" Diameter x 100' Long (38.1 mm x 30.5 m). Color Black. 1 roll. |
| Product Type | Dry-Shrink™ HSTT150-C Heatshrink, Black, Po, 100' L, 1.5" to |

Manufacturer Information

| | |
|---------------------------|----------------|
| Brand | Panduit® |
| GTIN | 00074983914937 |
| Manufacturers Part Number | HSTT150-C |
| UPC | 074983914937 |



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

12555 Harris Branch Pkwy Suite 105
78653-0000, TX Manor
Phone: 512-339-8750
Fax: 512-339-6732

Taxonomies, Classifications, and Categories

Type Heat-Shrink

Packaging

Carton 1

Weight Per roll 6.11

Uses, Certifications, and Standards

Application For Dry Locations;Insulating and protecting wires and cables

standard Mil Spec: AMS-DTL-23053/5 Class 1;UL: E122770