



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

711 Lake Bardwell Dr.
75119-0000, TX Ennis
Phone: 972-875-3413
Fax: 972-875-3174



K150 1 1/2 STR Liqtite Conn *Hubbell--Killark*

Catalog Number	K150
Manufacturer	Hubbell--Killark
Description	1 1/2" Straight Liquidtight Connector Non-Insulated
Weight per unit	0.7500 (lbs/each)
Product Category	Liquid Tight Fittings

Features

insulation	False
Insulation Type	Non-Insulated
Material	Steel

Material, Color, and Finish

Color	Gray
Finish	Zinc Plated

Dimensions and Weight

Length	2-3/8
Width	2-7/32

Descriptions

Description	1 1/2 STR LIQTITE CONN
extra long description	KLRK K150 1 1/2" STR LT CONNECTOR N
Long Description	1 1/2" Straight Liquidtight Connector Non-Insulated
Product Type	1 1/2" STR LT Connector Non-Insulated
Special Features	Liquidtight fittings are used with metallic and non-metallic conduit to seal out water, oil, and dust in applications food processors, beverage & chemical plants, plastics fabricators, machine shops, etc.

Manufacturer Information

Brand	KILLARK
GTIN	00783936991276
Manufacturers Part Number	K150
series	K Series
UPC	783936991276

Taxonomies, Classifications, and Categories

Category Description	FORM 5 CONDULETS, COVERS, & GASKETS
Type	Straight Liquidtight Non-Insulated Connector

Packaging

Carton	1
Package	1280
Weight Per each	0.75



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

711 Lake Bardwell Dr.
75119-0000, TX Ennis
Phone: 972-875-3413
Fax: 972-875-3174

Uses, Certifications, and Standards

Application

Use with metallic and non-metallic conduit to seal out water, oil, and dust in applications for food processors, beverage and chemical plants, plastics fabricators, machine shops, etc. Liquidtight connectors are also suitable for use in hazardous location

environmental conditions
standard

Hazardous locations
UL, CSA