



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

1612 E. Booth Road
72143-0000, AR Searcy
Phone: 501-368-0309
Fax: 501-368-0619



L820R R SGL 3W 20A 480V T/L B&W

Pass & Seymour/Legrand

| | |
|------------------|--|
| Catalog Number | L820R |
| Manufacturer | Pass & Seymour/Legrand |
| Description | Industrial Spec Grade Singleturnlok Registered 20A 480V Receptacle |
| Weight per unit | 0.2200 (lbs/each) |
| Product Category | Gen Purpose Recept & Surge Pro |

Features

| | |
|---------------------|--|
| amperage rating | 20 |
| connection | Back and side wire |
| indoor/outdoor | Indoor |
| Material | Nylon |
| Number of Wires | 3 |
| Outlet Type | Locking |
| Poles | 2 |
| Voltage | 480.0 V |
| Voltage Rating | 480 |
| Wall Plate Included | NO |
| Wattage | Electrical power is expressed in Amps and Volts. |
| Wire Size | 14 - 10 |

Dimensions and Weight

| | |
|--------|------|
| Height | 3.28 |
| Width | 1.19 |

Descriptions

| | |
|------------------------|---|
| Description | R SGL 3W 20A 480V T/L B&W |
| extra long description | P&S L820R TURNLOK REC |
| Features | Brass Mounting Strap |
| Long Description | Industrial Spec Grade SingleTurnlok Registered 20A 480V Receptacle |
| Product Type | Turnlok Rec |
| Special Features | Compact, impact-resistant nylon face and body are ultrasonically welded together for unrivaled strength. Face color coding by voltage facilitates locating and mating of proper devices. One piece, high-grade brass contacts offer excellent conductivity and heat-rise resistance. Clearly marked NEMA configuration, rating, and third-party listing on each unit's face. Single-piece, solid brass mounting strap is free of easily loosened rivets found on other brands. Side and external screw-pressure-plate back wire |



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

1612 E. Booth Road
72143-0000, AR Searcy
Phone: 501-368-0309
Fax: 501-368-0619

Manufacturer Information

| | |
|---------------------------|------------------|
| Brand | Pass and Seymour |
| GTIN | 00785007282054 |
| Manufacturers Part Number | L820-R |
| UPC | 785007282054 |

Taxonomies, Classifications, and Categories

| | |
|----------------------|----------------------------|
| Category Description | Industrial cord connectors |
| Type | Turnlok® Single Receptacle |

Trade Size

| | |
|----------|------|
| Amperage | 20.0 |
|----------|------|

Packaging

| | |
|-----------------|------|
| Carton | 1 |
| Package | 50 |
| Weight Per each | 0.22 |

Uses, Certifications, and Standards

| | |
|--------------------------|--|
| Application | Industrial |
| environmental conditions | Flammability: UL94 V2: Operating Temperature: Maximum continuous +75°C, minimum -40°C without impact |
| Mounting | WALL |
| nema rating | L8-20R |
| Operating Temperature | -40°-75°C |
| standard | CULUS, UL498, CSA C22.2 No. 42 |