



# ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

3706 Frankston Hwy  
75701-0000, TX Tyler  
Phone: 903-509-9882  
Fax: 903-509-9832



## LTB7590G 3/4" 90D LT Conn

Crouse-Hinds

Catalog Number	LTB7590G
Manufacturer	Crouse-Hinds
Description	Eaton Crouse-Hinds Series Liquidator Liquidtight Connector, FMC, 90° Angle, Aluminum Ground Lug, Insulated, #4-14 Awg Lug Size, Malleable Iron, 3/4"
Weight per unit	0.5900 (lbs/each)
Product Category	Liquid Tight Fittings

### Features

connection	Threaded
dimensions	2.1300 IN X 1.5600 IN X 2.1250 IN
installation type	THREADED

### Material, Color, and Finish

Color	MALLEABLE IRON
-------	----------------

### Descriptions

Description	3/4" 90D LT CONN
extra long description	MIDWEST LTB7590G 3/4 LT 90 DEG CONN
Features	Liquidtight fittings from Eaton's Crouse-Hinds Division are designed to protect conductors from mechanical damage due to vibration and movement while sealing out cutting oils, coolants, water, and dust. Typical applications include the wiring of machine tools, motors, transformers, food processing equipment, robotics, air conditioning units and illuminated signs. To meet any customer preference, Crouse-Hinds series liquidtight fittings are available in a variety sizes, configurations and materials, inclu
Long Description	Eaton Crouse-Hinds series Liquidator liquidtight connector, FMC, 90° angle, Aluminum ground lug, Insulated, #4-14 AWG lug size, Malleable iron, 3/4"
Product Type	3/4 LT 90 Deg Conn Ground Lug Insulated
Special Features	With 14 To 4 AWG Aluminum Grounding Lug

### Manufacturer Information

Brand	Eaton
GTIN	00784564264428
Manufacturers Part Number	LTB7590G
UPC	784564264428

### Taxonomies, Classifications, and Categories

Category Description	FORM 5 CONDULETS, COVERS, & GASKETS
Type	Liquidtight connector



# ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

3706 Frankston Hwy  
75701-0000, TX Tyler  
Phone: 903-509-9882  
Fax: 903-509-9832

## Trade Size

Trade Size ..... 3/4 in

## Packaging

Carton ..... 1

Package ..... 10

Weight Per each ..... 0.59

## Uses, Certifications, and Standards

Application ..... Commercial / Institutional Buildings / Structures - Commercial /  
Institutional Buildings / Structures - Other

standard ..... UL 467, UL 514B, CSA C22.88