ELLIOTT ELECTRIC SUPPLY
We Deliver...Lower Cost, Quality Products, & Personal Service
2310 N. Stallings Dr.
75964-0000, TX Nacogdoches
Phone: 936-569-7941
Fax: 936-560-4685

PN1014RD 12-10AWG 1/4"STD Nylon Insltd Ring TRML

Panduit Corporation

Catalog Number	PN1014RD
Manufacturer	Panduit Corporation
Description	The PN10-14R-D Pan-Term® Terminal Is A Nylon Insulated, Ring Terminal. The Metal Insulation Grip Sleeve Crimps to Wire Insulation, Providing Protection and Strain Relief to The Crimp Joint For High Vibration Applications. Internal Barrel Serrations Assure Good Wire Contact and Maximum Tensile Strength.
Weight per unit	0.0061 (lbs/each)
Product Category	Small Terminals & Connectors

Features

connection	Standard
insulation	Nylon
Material	Copper
media	Yes
Voltage Rating	600
Wire Size	10

Material, Color, and Finish

Color	Yellow
Finish	Tinned

Dimensions and Weight

Size	1/4"

Descriptions

Description	12-10AWG 1/4"STD NYLON INSLTD RING TRML
extra long description	PAN PN10-14R-D Pan-Term® PN10-14R-D
Long Description	The PN10-14R-D Pan-Term® Terminal is a nylon insulated, ring terminal. The metal insulation grip sleeve crimps to wire insulation, providing protection and strain relief to the crimp joint for high vibration applications. Internal barrel serrations assure good wire contact and maximum tensile strength.
Product Type	Pan-Term® PN10-14R-D Ring Terminal, Yellow, Nylon, 10-12 Awg

Manufacturer Information

Brand	Panduit®
GTIN	00074983800353
Manufacturers Part Number	PN10-14R-D
UPC	074983800353

ELLIOTT ELECTRIC SUPPLY
We Deliver...Lower Cost, Quality Products, & Personal Service
2310 N. Stallings Dr.
75964-0000, TX Nacogdoches
Phone: 936-569-7941
Fax: 936-560-4685

Taxonomies, Classifications, and Categories

Category Description	TERMINALS
Type	Ring Terminal

Availability

minimum qty	500

Packaging

Carton	500
Weight Per each	0.0061

Uses, Certifications, and Standards

Enclosure	Ring shape
Mounting	9/32
standard	cULus Listed 587H E52164, CSA Certified LR31212, Military QPL AS7928 (MS25036-157)
Temperature Rating	221 Degrees Fahrenheit (105 Degrees Celsius)