



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

204 Lake Road
76426-0000, TX Bridgeport
Phone: 940-683-5740
Fax: 940-683-5299



PT300 #300 Pin Terminal *Nsi Industries*

Catalog Number	PT300
Manufacturer	Nsi Industries
Description	Stranded Bi-Metallic Pin Terminal 300 MCM Stranded Bi-Metallic Pin Terminals Is Designed to Facilitate Termination Of Aluminum Conductors. Tin-Plated Stranded Copper Pin. Connector Bores Are Coated With Oxide Inhibitor. Supplied With Epdm Insulating Cover. Ul 486B Listed. Rated 600 Volts.
Weight per unit	0.4200 (lbs/each)
Product Category	Large Terminals & Connectors

Features

connection	4/0 Pin
insulation	Plastisol Cover
Material	Aluminum - Tin Plated Copper Pin
Number of Conductors	1
Poles	1
Voltage Rating	600 V
Warranty	1 YEAR

Material, Color, and Finish

Color	Brown
Finish	Aluminum

Dimensions and Weight

Size	L=4.08 - OD=1.16 - ID=.653 - Pin Dia=.523
------	---

Descriptions

Description	#300 PIN TERMINAL
extra long description	NSI PT300 Al Pin Terminal Cu Pin 30
Features	Stranded Bi-Metallic Pin Terminal 300 MCM Stranded Bi-Metallic Pin Terminals is designed to facilitate termination of aluminum conductors. Tin-plated stranded copper pin. Connector bores are coated with oxide inhibitor. Supplied with EPDM insulating cover. UL 486B listed. Rated 600 volts.
Long Description	Stranded Bi-Metallic Pin Terminal 300 MCM Stranded Bi-Metallic Pin Terminals is designed to facilitate termination of aluminum conductors. Tin-plated stranded copper pin. Connector bores are coated with oxide inhibitor. Supplied with EPDM insulating cover. UL 486B listed. Rated 600 volts.
Product Type	Al Pin Terminal Cu Pin 300 MCM
Special Features	300 MCM (STR) - 4/0 CU Pin Size



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

204 Lake Road
76426-0000, TX Bridgeport
Phone: 940-683-5740
Fax: 940-683-5299

Manufacturer Information

Brand	Polaris
GTIN	00662381033093
Manufacturers Part Number	PT300
UPC	662381033093

Taxonomies, Classifications, and Categories

Category Description	TERMINALS
Type	Bi-Metallic Pin

Packaging

Carton	1
Weight Per each	0.42

Uses, Certifications, and Standards

Application	Terminate, Splice, Tap Power Connectors
environmental conditions	90 C
standard	UL486A/B
Temperature Rating	90 C