

# Specifications



Photo is representative



## Eaton S811+N37N3S

Eaton S811+ soft starter, 65mm 37 A with OPT Inside the Delta

### General specifications

<b>PRODUCT NAME</b>	Eaton S811+ soft starter
<b>CATALOG NUMBER</b>	S811+N37N3S
<b>UPC</b>	786685558899
<b>PRODUCT LENGTH/DEPTH</b>	11 in
<b>PRODUCT HEIGHT</b>	11.5 in
<b>PRODUCT WIDTH</b>	9 in
<b>PRODUCT WEIGHT</b>	7.8 lb
<b>CERTIFICATIONS</b>	Contact Manufacturer
<b>PRODUCT TYPE</b>	Soft starter

## Product specifications

<b>AMPERAGE RATING</b>	37A
<b>SPECIAL FEATURES</b>	30 second ramp or 450% current limit at 50°C, inside-the-delta connection
<b>TYPE</b>	Severe duty
<b>FRAME SIZE</b>	N
<b>RATING</b>	10 kW at 230 V, 18.5 kW at 380-400 V, 18.5 kW at 440 V

## Resources

<b>CATALOGS</b>	<a href="#">Solid-State Motor Control, Reduced Voltage Motor Starters, Volume 6, Tab 1</a> <a href="#">eaton-drives-soft-starter-catalog-ca04020001zen-us.pdf</a>
<b>MULTIMEDIA</b>	<a href="#">Soft Starter Product Family Overview</a> <a href="#">Soft Starter DS7 up to 32 A</a> <a href="#">Soft starter DS7 up to 200 A</a>
<b>SPECIFICATIONS AND DATASHEETS</b>	<a href="#">Eaton Specification Sheet - S811+N37N3S</a>
<b>WARRANTY GUIDES</b>	<a href="#">Selling Policy 25-000 - Distribution and Control Products and Services</a>

**PROJECT NAME:**

**PROJECT NUMBER:**

**PREPARED BY:**

**DATE:**



**Eaton Corporation plc** Eaton House  
30 Pembroke Road  
Dublin 4, Ireland  
Eaton.com

© 2026 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.



# Specifications



Photo is representative



## Eaton S811+N37N3S

Eaton S811+ soft starter, 65mm 37 A with OPT Inside the Delta

### General specifications

<b>PRODUCT NAME</b>	Eaton S811+ soft starter
<b>CATALOG NUMBER</b>	S811+N37N3S
<b>UPC</b>	786685558899
<b>PRODUCT LENGTH/DEPTH</b>	11 in
<b>PRODUCT HEIGHT</b>	11.5 in
<b>PRODUCT WIDTH</b>	9 in
<b>PRODUCT WEIGHT</b>	7.8 lb
<b>CERTIFICATIONS</b>	Contact Manufacturer
<b>PRODUCT TYPE</b>	Soft starter



Powering Business Worldwide

## Product specifications

<b>AMPERAGE RATING</b>	37A
<b>SPECIAL FEATURES</b>	30 second ramp or 450% current limit at 50°C, inside-the-delta connection
<b>TYPE</b>	Severe duty
<b>FRAME SIZE</b>	N
<b>RATING</b>	10 kW at 230 V, 18.5 kW at 380-400 V, 18.5 kW at 440 V

## Resources

<b>CATALOGS</b>	<a href="#">Solid-State Motor Control, Reduced Voltage Motor Starters, Volume 6, Tab 1</a> <a href="#">eaton-drives-soft-starter-catalog-ca04020001zen-us.pdf</a>
<b>MULTIMEDIA</b>	<a href="#">Soft Starter Product Family Overview</a> <a href="#">Soft Starter DS7 up to 32 A</a> <a href="#">Soft starter DS7 up to 200 A</a>
<b>SPECIFICATIONS AND DATASHEETS</b>	<a href="#">Eaton Specification Sheet - S811+N37N3S</a>
<b>WARRANTY GUIDES</b>	<a href="#">Selling Policy 25-000 - Distribution and Control Products and Services</a>

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

DATE:



**Eaton Corporation plc** Eaton House  
30 Pembroke Road  
Dublin 4, Ireland  
Eaton.com

Follow us on social media to get the latest product and support information.



© 2026 Eaton. All Rights Reserved.