

Kellems® Wire Management Products
Straight Male Cord Connectors
Cord Connectors

HUBBELL

Features

- Nylon cord connector resists most common industrial corrosives
- Provides effective pullout protection
- Lightweight design

Ordering Information

Description	Color Code	UPC	Catalog Number
Cord Connectors, Straight Male, Nylon, Gray	Blue	783585208053	SHC1023CR



Listings

UL Listed
CSA Certified

Online Resources

[eCatalog](#)

Specifications

Material	Gray Nylon
Form Size	F2
NPT Hub Size	1/2 Inch
Cord Diameter Range Inches (mm)	.38"- .50" (9.7-12.7)

Performance

Environmental

Flammability	UL 94-V2
Hazardous Locations	Used in hazardous locations per Class I Div. 2, Class II Div. 1 & 2, Class III Div. 1 & 2 in accordance with the NEC
Operating Temperatures	-30°F to +225°F (-34°C to +107°C)

Kellems® Wire Management Products
Straight Male Cord Connectors
Cord Connectors

HUBBELL

Features

- Nylon cord connector resists most common industrial corrosives
- Provides effective pullout protection
- Lightweight design

Ordering Information

Description	Color Code	UPC	Catalog Number
Cord Connectors, Straight Male, Nylon, Gray	Blue	783585208053	SHC1023CR



Listings

UL Listed
CSA Certified

Online Resources

[eCatalog](#)

Specifications

Material	Gray Nylon
Form Size	F2
NPT Hub Size	1/2 Inch
Cord Diameter Range Inches (mm)	.38"- .50" (9.7-12.7)

Performance

Environmental

Flammability	UL 94-V2
Hazardous Locations	Used in hazardous locations per Class I Div. 2, Class II Div. 1 & 2, Class III Div. 1 & 2 in accordance with the NEC
Operating Temperatures	-30°F to +225°F (-34°C to +107°C)

