



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

110 Success Blvd
79029-0000, TX Dumas
Phone: 806-934-4805
Fax: 806-717-2052



SKAB250 250MCM Al/Cu Butt Splice

Nsi Industries

Catalog Number	SKAB250
Manufacturer	Nsi Industries
Description	Easy-Splice Dual Rated Direct Burial Butt Splice Kit For 1/0 Awg to 250 MCM Utilizing A Mechanical Dual Rated Splice and Matched Heavy Wall Heat Shrink Tubing to Create An Insulated Splice For Copper and/or Aluminum Cables. Temperature Rating: 105 Degrees C. 600 Volt Maximum.
Weight per unit	0.3760 (lbs/each)
Product Category	Splicing & Terminating Kits

Features

Cable Size	1/0 AWG-250 MCM
Cable Type	Class A-B
insulation	Heat Shrink
Voltage Rating	600 V
Warranty	1 YEAR

Material, Color, and Finish

Color	Black
-------	-------

Descriptions

Description	250MCM AL/CU BUTT SPLICE
extra long description	NSI SKAB-250 Direct Burial Splice K
Features	Easy-Splice Dual Rated Direct Burial Butt Splice Kit for 1/0 AWG to 250 MCM Utilizing a mechanical dual rated splice and matched heavy wall heat shrink tubing to create an insulated splice for copper and/or aluminum cables. Temperature Rating: 105 degrees C. 600 Volt Maximum.
Long Description	Easy-Splice Dual Rated Direct Burial Butt Splice Kit for 1/0 AWG to 250 MCM Utilizing a mechanical dual rated splice and matched heavy wall heat shrink tubing to create an insulated splice for copper and/or aluminum cables. Temperature Rating: 105 degrees C. 600 Volt Maximum.
Product Type	Direct Burial Splice Kit 1/0 Awg - 250 MCM
Special Features	Dual Rated For Use With Copper And Aluminum Cable

Manufacturer Information

Brand	Polaris
GTIN	00662381169167
Manufacturers Part Number	SKAB-250
UPC	662381169167

Taxonomies, Classifications, and Categories

Type	Direct Burial Splice Kit With Heat Shrink
------	---



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

110 Success Blvd
79029-0000, TX Dumas
Phone: 806-934-4805
Fax: 806-717-2052

Packaging

Carton	1
Weight Per each	0.376

Uses, Certifications, and Standards

Application	Splicing Wire
Operating Temperature	-40 C To 90 C