

Specifications



Eaton TCF60

Eaton Bussmann Series Class CF fuse, TCF, time-delay, dual-element current limiting cube fuse, 60 A, indicating fuse, interrupting rating of 100 kA at 300 Vdc and 300 kA at 600 Vac

General specifications

| | |
|-----------------------------|---|
| PRODUCT NAME | Eaton Bussmann series TCF fuse |
| CATALOG NUMBER | TCF60 |
| UPC | 051712615082 |
| EAN | 5027590184441 |
| PRODUCT LENGTH/DEPTH | 2.13 in |
| PRODUCT HEIGHT | 1.9 in |
| PRODUCT WIDTH | 1 in |
| PRODUCT WEIGHT | 0.17 lb |
| WARRANTY | Not Applicable |
| COMPLIANCES | CE Marked RoHS Compliant |
| CERTIFICATIONS | UL Listed CSA Certified |



Powering Business Worldwide

Electrical rating

| | |
|-------------------------------|--|
| AMPERAGE RATING | 60 A |
| FREQUENCY RATING - MAX | 60 Hz |
| FREQUENCY RATING - MIN | 50 Hz |
| INTERRUPT RATING | 300 kAIC at 600 Vac 100 kAIC at 300 Vdc |
| RESPONSE TIME | 10 sec at 500% |
| VOLTAGE RATING | 600 Vac, 300 Vdc |

General information

| | |
|-------------------------|---------------------------|
| CLASS | Class CF |
| CONNECTION | Blade end |
| FUSE INDICATOR | With Indicator |
| MOUNTING METHOD | Chassis 35 mm DIN rail |
| SPECIAL FEATURES | Finger safe |
| USED WITH | TCFH60N, CCP2-3-60CF |

Physical details

| | |
|---------------------------|------------------------|
| COLOR | Black |
| FUSE TYPE | Class CF Time delay |
| MATERIAL | Glass filled PES |
| NUMBER OF ELEMENTS | Dual |
| PACKAGING TYPE | Standard |

Resources

| | |
|------------------------|---|
| CATALOGS | Low Voltage Branch Circuit Fuse Chapter Bussmann Full Line Catalog |
| COMPLIANCE INFORMATION | RoHS Search Tool The Power of Space |
| MULTIMEDIA | Bussmann series Fuseology |
| TECHNICAL DATA SHEETS | Bussmann series UL Class CF CUBEFuse data sheet no. 9000 |

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

DATE:



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

Follow us on social media to get the latest product and support information.



© 2025 Eaton. All Rights Reserved.

Specifications



Eaton TCF60

Eaton Bussmann Series Class CF fuse, TCF, time-delay, dual-element current limiting cube fuse, 60 A, indicating fuse, interrupting rating of 100 kA at 300 Vdc and 300 kA at 600 Vac

General specifications

| | |
|-----------------------------|---|
| PRODUCT NAME | Eaton Bussmann series TCF fuse |
| CATALOG NUMBER | TCF60 |
| UPC | 051712615082 |
| EAN | 5027590184441 |
| PRODUCT LENGTH/DEPTH | 2.13 in |
| PRODUCT HEIGHT | 1.9 in |
| PRODUCT WIDTH | 1 in |
| PRODUCT WEIGHT | 0.17 lb |
| WARRANTY | Not Applicable |
| COMPLIANCES | CE Marked RoHS Compliant |
| CERTIFICATIONS | UL Listed CSA Certified |



Powering Business Worldwide

Electrical rating

| | |
|-------------------------------|--|
| AMPERAGE RATING | 60 A |
| FREQUENCY RATING - MAX | 60 Hz |
| FREQUENCY RATING - MIN | 50 Hz |
| INTERRUPT RATING | 300 kAIC at 600 Vac 100 kAIC at 300 Vdc |
| RESPONSE TIME | 10 sec at 500% |
| VOLTAGE RATING | 600 Vac, 300 Vdc |

General information

| | |
|-------------------------|---------------------------|
| CLASS | Class CF |
| CONNECTION | Blade end |
| FUSE INDICATOR | With Indicator |
| MOUNTING METHOD | Chassis 35 mm DIN rail |
| SPECIAL FEATURES | Finger safe |
| USED WITH | TCFH60N, CCP2-3-60CF |

Physical details

| | |
|---------------------------|------------------------|
| COLOR | Black |
| FUSE TYPE | Class CF Time delay |
| MATERIAL | Glass filled PES |
| NUMBER OF ELEMENTS | Dual |
| PACKAGING TYPE | Standard |

Resources

| | |
|------------------------|---|
| CATALOGS | Low Voltage Branch Circuit Fuse Chapter Bussmann Full Line Catalog |
| COMPLIANCE INFORMATION | RoHS Search Tool The Power of Space |
| MULTIMEDIA | Bussmann series Fuseology |
| TECHNICAL DATA SHEETS | Bussmann series UL Class CF CUBEFuse data sheet no. 9000 |

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

DATE:



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

Follow us on social media to get the latest product and support information.



© 2025 Eaton. All Rights Reserved.