



# ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

303 East Harned Avenue  
74075-0000, OK Stillwater  
Phone: 405-880-8633  
Fax: 405-880-8634



## WGRB Wingtwistgrounding Connector, WGR Green, 250/Carton

*Ideal*

Catalog Number	WGRB
Manufacturer	Ideal
Description	Ideal WGR-B WGR Green Ground Cap 25
Weight per unit	0.0070 (lbs/each)
Product Category	Electrical Fixture Conn ( Nuts

### Features

Material	Flame-retardant Polypropelene
Voltage Rating	600

### Material, Color, and Finish

Color	Green
-------	-------

### Descriptions

Description	WINGTWISTGROUNDING CONNECTOR,WGR GREEN,250/CARTON
Features	With a full line for virtually every wire size and combination, the WingTwist Wire Connector offers a great combination of performance and value.The contoured wing design of the WingTwist provides maximum torque for a variety of electrical applications while the copolymer shell and live-action spring expand for smooth, progressive tightening providing dependable connections.With a tough, flame-retardant shell that withstands environmental extremes, and a long, deep skirt to provide maximum dielectric prote
Long Description	IDEAL WGR-B WGR GREEN GROUND CAP 25
Product Type	WGR Green Ground Cap 250 Box
Special Features	1,000V Maximum In Fixtures And Signs;Contoured Wing Design Provides Maximum Torque;Deep Skirt Protects Against Flash-Over;Expanding, Square-Wire Spring Creates Secure Connections;Features: Five Color-Coded Models Cover Common Construction Wire Ranges And Combinations, Including Grounding;Model Number: WGR

### Manufacturer Information

Brand	Buchanan
GTIN	00781789470078
Manufacturers Part Number	WGR-B
UPC	781789470078

### Taxonomies, Classifications, and Categories

Category Description	WIRE NUTS
----------------------	-----------



# ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

303 East Harned Avenue  
74075-0000, OK Stillwater  
Phone: 405-880-8633  
Fax: 405-880-8634

## Availability

Manufacturer Status	Inactive
minimum qty	250
Status	Inactive

## Packaging

Carton	250
Weight Per each	0.007

## Uses, Certifications, and Standards

Application	For Grounding And Bonding Applications
environmental conditions	Tough, UL 94V-2 Flame-Retardant Shell Rated At 105 DEG C (221 F)
standard	CSA C22.2 #188, UL 467 Listed, RoHS