



On-Q
Category 5e RJ45 Keystone Connector, Ivory
Part No. WP3450IV



Enhance your network setup with this high-quality Category 5e RJ45 Keystone Connector in ivory. Designed for easy punchdown termination, this vertical insert ensures secure and reliable connections. Compatible with all Keystone wall plates, it features rear retention caps for secure wire termination and meets Category 5e performance standards.

Features & Benefits

Ensures Category 6 performance standard compliance	Rear retention caps ensure secure wire termination
Vertical design for easy punchdown termination	T568A and T568B wiring labels included
Meets Category 5e described in TIA/EIA-568-B.2	Insertion and extraction life is 750 Cycles Min
Jack housing is high-impact, flame resistant plastic, UL 94V-0	Spring wire is phosphor bronze alloy plated with 50 micro-inch of gold over 100 micro-inches of nickel
Also available in contractor pack of 50 (WP3450-WH-50)	

Specifications

General Info

Product Line	On-Q	Color	Ivory
UPC Number	804428024859	Country Of Origin	Taiwan, Province Of China
Application Sector	Residential	Standard	CSA, cULus, RoHS, ANSI/UL 1863, Flame-Retardant Plastic UL 94V-0

Dimensions

Product Width US	0.64 in	Product Height US	0.87 in
Product Length US	1.28 in		

Technical Information

Termination Style	Punchdown	Cable Type	Cat5e
Environmental Conditions	0 to 93% (relative humidity, non-condensing)		



On-Q
Category 5e RJ45 Keystone Connector, Ivory
Part No. WP3450IV



Enhance your network setup with this high-quality Category 5e RJ45 Keystone Connector in ivory. Designed for easy punchdown termination, this vertical insert ensures secure and reliable connections. Compatible with all Keystone wall plates, it features rear retention caps for secure wire termination and meets Category 5e performance standards.

Features & Benefits

Ensures Category 6 performance standard compliance

Rear retention caps ensure secure wire termination

Vertical design for easy punchdown termination

T568A and T568B wiring labels included

Meets Category 5e described in TIA/EIA-568-B.2

Insertion and extraction life is 750 Cycles Min

Jack housing is high-impact, flame resistant plastic, UL 94V-0

Spring wire is phosphor bronze alloy plated with 50 micro-inch of gold over 100 micro-inches of nickel

Also available in contractor pack of 50 (WP3450-WH-50)

Specifications

General Info

Product Line	On-Q	Color	Ivory
UPC Number	804428024859	Country Of Origin	Taiwan, Province Of China
Application Sector	Residential	Standard	CSA, cULus, RoHS, ANSI/UL 1863, Flame-Retardant Plastic UL 94V-0

Dimensions

Product Width US	0.64 in	Product Height US	0.87 in
Product Length US	1.28 in		

Technical Information

Termination Style	Punchdown	Cable Type	Cat5e
Environmental Conditions	0 to 93% (relative humidity, non-condensing)		
